

1 1/2" SaberJet Nozzle with Pistol Grip (DSO)

STYLE 1520

The patented Dual Shutoff SaberJet is our original multipurpose nozzle with both solid bore penetration and fog stream capability, available with a 1/2" or 5/8" (13, 16 mm) smooth bore tip.

Patent #6,877,676

Features

The Dual Shutoff SaberJet fire hose nozzles can operate efficiently at pressures as low as 50 psi for reduced firefighter fatigue, or up to 100 psi for maximum flow. This versatile, multi-purpose fire nozzle is well suited for multiple applications, including for use with water and foam.

- Compatible with Quick-Attack Foam Tube Style 796
- Comes with pistol grip
- Tip Options: 1/2", 5/8" (must specify)
- Tip Options: 12 mm, 16 mm (must specify)
- Fog flow at 100 psi (7 bar): 95 GPM (360 LPM)



Specifications

Style	1520
Certification(s)	
Warranty	
Weight	5 3/8 lbs (2.4 kg)
Type	Combination Fog/Smooth Bore
Material	Pyrolite
Brand	SaberJet
Swivel Inlet	1 1/2" (38 mm)
Length	10 1/2" (267 mm)
Width	4 1/4" (108 mm)
Height	10 1/4" (203 mm)

1 1/2" SaberJet Nozzle with Pistol Grip (DSO)

STYLE 1520



1 1/2" SaberJet Nozzle with Pistol Grip (DSO)

STYLE 1520

Akron Brass 1-1/2" Dual Shutoff SaberJet Nozzle Specification

A combination solid stream and fog nozzle with the capability to flow either stream independently or simultaneously. The solid bore shall have field changeable tips with orifices of either 1/2", 5/8", and the fog shall flow at 100 psi (7 bar): 95 GPM (360 LPM) . The nozzle shall have a pistol grip, spinning teeth, multiple pattern detents, flush without shutting down, twist shutoff of the fog stream, and a full time swivel inlet. The bale shutoff of the smooth bore shall be with dual drive trunnions. The nozzle shall also be constructed of lightweight Pyrolite, have a shutoff ball with flow diversion for the fog waterway, have a 10 year warranty and meet NFPA 1964.