



1.800.228.1161 | akronbrass.com | akroncare@idexcorp.com

Copyright 2021 Akron Brass Company. All rights reserved. No portion of this can be reproduced without the express written consent of the Akron Brass Company. (04/21)

1" ProVenger SG Fire Hose Nozzle

STYLE 1602



1" ProVenger SG Fire Hose Nozzle

STYLE 1602

Style 1602 (Selectable gallonage)

A Lightweight fog and straight stream nozzle with multiple gallonage settings shall be provided. The nozzle shall have spinning turbine teeth, feature multiple flow indicating detents for 5-10-20-40 gpm (19-40-75-150 lpm) at 75 or 100 psi (5, 6 or 7 bar) and 12-23-34-53 gpm (45- 85-130-200 lpm) at 87 psi (6 bar), a one-piece solid nylon reinforced bumper, one-piece solid rubber-like handle with dual stops, dual drive trunnions, and an extruded single piece Pyrolite body. The nozzle shall have an optional solid rubber-like pistol grip that can be easily removed. The nozzle also shall have a minimum 100° fog pattern, a fulltime swivel inlet, be capable of flushing without shutting down or changing stream patterns, and a 5 year warranty. The nozzle must meet all aspects of NFPA 1964 with test results available. 6 bar must meet CE.