

Aries™ Monitor

Single handwheel brass monitor for controlled elevation, 90° above to 60° below horizontal. Cast-in turning vanes for more efficient flow.

- 3525 Aries Monitor**
- Full 3" waterway
 - Optional drain valve - Must specify

Style	Weight lbs. (kg)	Height	Width	Inlet	Outlet	Flow	
						GPM	LPM
3525	66 (30 kg)	15" (38 cm)	14" (55 cm)	3" or 4" FL (7.6 or 10.2 cm)	2 1/2" (6.4 cm)	1250	4800

Style 3525
Shown with Style 4450
Aquastream™ Nozzle



Gemini™ Monitor

A self-locking dual handwheel brass monitor with a split waterway and cast-in turning vanes for efficient flow. Built-in pressure gauge and gauge guard.

- 3471 Gemini Monitor**
- 135° vertical travel

Style	Weight lbs. (kg)	Height	Width	Inlet	Outlet	Flow	
						GPM	LPM
3471	75 (34 kg)	20" (50.8 cm)	13 1/4" (33.5 cm)	3" - 4" (7.6-10.1 cm) NPT or FL	2 1/2" (6.4 cm)	1000	3800

Style 3471
Shown with
Style 3488
Discharge Pipe
& Style 489 Tip



Conquest™ Monitor

A dual handwheel brass monitor with cast-in turning vanes for industrial fires and vapor releases.

- 3671 Dual Handwheel Conquest Monitor**
- Low friction loss
 - Full 4" waterway
 - 12 volt electric version available

Style	Weight lbs. (kg)	Height	Width	Inlet	Outlet	Flow	
						GPM	LPM
3671	185 (48 kg)	21 1/2" (54.6 cm)	17" (43.1 cm)	4" FL (10.1 cm)	3 1/2" NH (8.9 cm)	2000	7600

Style 3671
Shown with
Style 5071
Akromatic®
Nozzle

