

ALARM MOBILE UNITS



The ALARM mobile extinguisher range is deployed in high risk areas where there is a possible lack of additional fire fighting cover.

Mobile units are available with AFFF Foam, Protein Foam, Multi-purpose ABC Powder.

It's design has been specifically aimed at protecting Helicopter and light aircraft engines.

FIXED BASE

Fixed base equipment, suitable for deck/vehicle mounting or system holding tanks.

ALARM MOBILE AFFF & ABC POWDER UNITS

EXTINGUISHER CODA	AAF125	AAF150	AAT125	AAT150
PROPELLANT TYPE	Stored Pressure			
CHEMICAL EXTINGUISHANT	AFFF POWDER		ABC POWDER Mono Ammonium Phosphate	
CAPACITY	25Ltr	50Ltr	25 kg	50kg
PAINT PRIMER/FINISH	Polyester			
PAINT COLOUR	Body Red (RAL 3020)			
FIRE CLASS	A - B Types		ABC Types + Electrical	
FIRE RATING	+1° C to + 60° C		-20° C to + 60° C	
TEST PRESSURE	30 Bar			
OPERATING PRESS. AT. 20° C	12 Bar	15 Bar	12 Bar	15 Bar
MIN. DISCHARGE TIME	30 Secs	42 Secs	30 Secs	42 Secs
DISCHARGE RANGE	12 Metres	14 Metres	12 Metres	14 Metres
SAFE OPERATING DISTANCE	6 Metres			
CYLINDER	4.00 mm HRP steel			
OPERATING VALVE	Zinc Alloy BS1004			
HEIGHT	950 mm	1115 mm	950 mm	1115 mm
DIAMETER	250 mm	320 mm	250 mm	320 mm
FULL	60.250 kg	92.300 kg	60.250 kg	92.300 kg
EMPTY	22.800 kg	30.00 kg	22.800 kg	30.00 kg
* - APPROVED TO TS EN 3	*	*	*	*



K-Q
TS - EN - ISO
9002