

ABC POWDER


MULTI-PURPOSE ABC Powder is a truly versatile extinguisher which is used to extinguish Class A (carbonaceous) fires achieved by sealing the burning embers. It is also used on Class B (flammable liquid) fires. (There is no requirement for Class C (flammable gas) fires Under TS EN 3 and Electrical.)

The 1 kg, extinguishers are available as stored pressure type only, with an acetal plastic operating head.

ABC POWDER extinguishers are identified by the unique coloured hose, designed to TS EN 3.



ABC POWDER IDENTIFICATION COLOUR



K-Q
TS - EN - ISO
9002

ABC POWDER

EXTINGUISHER CODA	ATK6	ATK12	ATIB6	ATIB12
PROPELLANT TYPE	115gm Co ₂ Gas Cartridge	150gm	Stored Pressure	
CHEMICAL EXTINGUISHANT	ABC Dry Powder Mono-Ammonium Phosphate & Ammonium Sulphate			
CAPACITY	6kg	12kg	6kg	12kg
PAINT PRIMER/FINISH	Iron Phosphate/Polyester			
PAINT COLOUR	Body Red (RAL 3000) Hose French Blue (RAL 5002)			
FIRE CLASS	A - B - C Types + Electrical			
FIRE RATING	27A / 183B/C	43A / 233B/C	27A / 183B/C	43A / 233B/C
OPERATING TEMP.	- 20° C to + 60° C			
TEST PRESSURE	30 Bar			
OPERATING PRESS. AT. 20° C	12.5 Bar	12.5 Bar	12.5 Bar	12.5 Bar
MIN. DISCHARGE TIME	17 Secs	32 Secs	15 Secs	17 Secs
DISCHARGE RANGE	5 metres	7 metres	5 metres	7 metres
SAFE OPERATING DISTANCE	2 Metres			
CYLINDER	2.00 mm Mild Steel Grade CCRS 6114			
OPERATING VALVE	Acetal Plastic		Diecast ZA5 Zinc Alloy BS 1004	
HEIGHT	530 mm	610 mm	535 mm	625 mm
DIAMETER	149 mm	169 mm	149 mm	169 mm
FULL	10.3 kg	18.25 kg	10.5 kg	18.15 kg
EMPTY (Excluding cartridge)	4.3 kg	6.25 kg	4.3 kg	6.15 kg
CARTON SIZE	215x160x 550mm	215x200x 640mm	215x160x 550mm	215x200x 640mm
* - APPROVED TO TS EN 3	*	*	*	*
STAINLESS STEEL BODIES AVAILABLE ON REQUEST				