


AMK-30CRT SPREADER

Part Number 300204462000



Optional Accessory:
Quick Adjust Chain Package
Part No. 391200001000



Optional Accessory:
Extended Reach Tip
Part No. 391000001010
Order (2) for a pair
(Increase the spread up to 8 in.)

SPECIFICATIONS

Maximum Spreader Opening:	32.0 in.	(813 mm)
Maximum Spreader Force :	17,775 lbs.	(79.1 kN)
(measured at 30.2 in. (767mm) spreader tip opening)		
Weight (Ready-to-use):	48.0 lbs.	(21.75 kg)
Length:	30.1 in.	(765 mm)
Width:	12.0 in.	(305 mm)
Depth:	8.2 in.	(208 mm)
Rated Input Pressure:	10,500 psi	(724 bar)

DESIGN & OPERATIONAL FEATURES

- ★ *Unique construction allows maximum usable force*
- ★ *Tips remain parallel to the cylinder throughout the spread allowing them to stay in contact with the material continuously for maximum spread (helps avoid piercing with the tips)*
- ★ *Removable tips to accept chain package and optional tips for versatility*
- ★ *Push button pins for easy removal of tips (eliminates possibility of losing pins in the field)*



2700 Wisconsin Avenue, Downers Grove, IL 60515-4226
Tel. (630) 515-1800 Fax (630) 515-8866
Website <http://www.amkus.com> E-mail experts@amkus.com