

Chubb FX Range – FX HydroSpray

Protecting your world



Model	HY3	HY6
Product No.	7926/00	7927/00
Height (mm)	431	561
Width (mm)	302	316
Shell Diameter (mm)	130	150
Capacity (litres)	3	6
Test Pressure (bar)	33	33
Working Pressure at 20°C	15	15
Weight Full (kg)	5.5	9.6
Weight Empty (kg)	2.4	3.41
Discharge Time at 20°C (secs)	25-30	55-65
Minimum Effective Discharge (%)	90	90
Temperature Range (°C)	+5 to +60	+5 to +60
Fire Rating	13A	21A

DO NOT ADD FREEZE PROTECTION

Class of fire



Fires involving freely burning materials. For example wood, paper, textiles and carbonaceous materials.

Method of use

WATER with ADDITIVE: Apply the spray over the area of the fire, moving it from side to side, until the fire is extinguished.

Call **0800 32 1666**

www.chubb.co.uk

© Chubb Fire & Security Limited 2016

This briefing is intended as general guidance and is not a substitute for detailed advice in specific circumstances. Although great care has been taken in the compilation and preparation of this edition to ensure accuracy, Chubb cannot in any circumstances accept responsibility for errors, omissions or advice given or for any losses arising from reliance upon information contained in this publication.

Chubb Fire & Security