

## Description

Fomtec EXT Ultra is an aqueous film forming foam concentrate (AFFF) consisting of fluorocarbon and hydrocarbon surfactants blended with various solvents, preservatives and stabilisers.

The foam forms an aqueous film that rapidly cuts off the oxygen supply and thus knocks down the fire. The expanded foam from which the film is drained forms a stable blanket that suppresses the release of flammable vapours and cools down the fuel surface extinguishing the fire and preventing re-ignition.

The low surface tension of the water foam concentrate solution enables the aqueous film, although heavier than the burning liquid, to float on top of the liquid surface.

Fomtec should be used at minimum 1% concentration (1 part concentrate in 99 parts of water). If high rating is to be achieved the concentration can be increased.

## Application

Fomtec EXT Ultra has been developed specially for use in extinguishers.

## Fire Performance & Foaming

The fire performance of Fomtec EXT Ultra has been tested in accordance with EN 3 using commercial foam extinguishers.

## Compatibility

Contact one of the Fomtec sales team with questions.

## Environmental impact

Fomtec EXT Ultra is formulated using raw materials specially selected for their fire performance and their environmental profile. Fomtec EXT Ultra is biodegradable. The handling of spills of concentrate or foam solution should however be undertaken according to local regulations. Normally sewage systems can dispose foam solution based on this type of foam concentrate, but local sewage operators should be consulted in this respect. This product contains NO PFOS or PFOA.

Full details will be found in the Material Safety Datasheet (MSDS).

## Technical data

Appearance	Clear yellowish liquid
Specific gravity at 20°C	1,095 +/- 0.01 g/ml
Viscosity at 20°C	≤ 30 mPas
pH	6,5 – 8,5
Freezing point	0°C
Recommended storage temperature	0 - 55°C
Suspended sediment (v/v)	Less than 0,2%
Surface tension approx.	18,0 dynes/cm

## Storage / Shelf life

Stored in original unbroken packaging the product will have a long shelf life. Shelf life in excess of 10 years will be found in temperate climates. As with all foams, shelf life will be dependent on storage temperatures and conditions. If the product is frozen during storage or transport, thawing will render the product completely usable.

Synthetic foam concentrates should only be stored in stainless steel or plastic containers. Since electrochemical corrosion can occur at joints between different metals when they are in contact with foam concentrate, only one type of metal should be used for pipelines, fittings, pumps, and tanks employed in the storage of foam concentrates. We recommend following our guidelines for storage and handling ensuring favourable storage conditions.

## Packaging

We supply this product in 25 litre cans and 200 litre drums. We can also ship in 1000 litre containers or in bulk.

Litres per piece	Packaging	Part no
25 litres	Can	15-9020-01
200 litres	Drum	15-9020-02
1000 litres	Container	15-9020-04
Bulk	Special request	

## International Approvals

- EN 3