

STHAMEX-AFFF 1% F-15

Aqueous film forming fire extinguishing foam concentrate

Description

STHAMEX-AFFF 1% F-15 is a high concentrated, aqueous film forming fire extinguishing foam based on surface active agents. A combination of fluoric components, foam stabilisers and antifreezing compounds provides for its outstanding efficiency.

by the foam and prevents reignition should the foam blanket get ruptured. The foam is oil-repellent (oleophobic), i.e. it does not load itself with petroleum products and is, therefore ideal for sub-surface foam application.

Properties

STHAMEX-AFFF 1% F-15 is designed for generating low expansion foam and owing to its high foam density long throwing distances are achieved.

STHAMEX-AFFF 1% F-15 foam safely extinguishes class A + B fires and forms a gastight cover on liquid surfaces. It is stable on fuels with proportions of polar additives like alcohol and other additives. **STHAMEX-AFFF 1% F-15** complies with applicable standards.

STHAMEX-AFFF 1% F-15 forms foam very readily and is therefore also suitable for use in foam/water sprinkler systems.

The high water releasing capacity favours film formation, increases flowability, reduces the extinction time and cools the source of fire. The aqueous film extinguishes fires even in areas not yet reached

| | | |
|---|--|-------------------|
| Recommended induction rate | low expansion foam | 1.0 % |
| Foam expansion (according to DIN EN 1568) | low expansion foam | ≤ 15 times |
| 25% water drainage time/ 50% water drainage time (according to DIN EN 1568) | low expansion foam | ≤ 5 / ≤ 8 minutes |
| Density | 1.07 ± 0.02 kg/l | |
| Frost resistance | -15 °C | |
| pH value | 6.5 to 8.5 | |
| Sediment content | none | |
| Spreading coefficient | ≥3 mN/m | |
| Viscosity (according to DIN EN 1568) | 20°C ≤ 20 mm ² /s 0°C ≤ 40 mm ² /s -15°C ≤ 120 mm ² /s | |
| Environmental acceptability | STHAMEX-AFFF 1% F-15 is physiologically harmless and biodegradable. | |
| Special notes | STHAMEX-AFFF 1% F-15 is not detrimental to health, provided it is used for the intended purpose. Fire extinguishing exercises and tests may have to be coordinated with the local authorities. When persons are sprayed with foam, please bear in mind that they will not be able to breathe while covered with foam. For further information to refer to the safety data sheet. users are asked | |

Physical properties and technical data

STHAMEX-AFFF 1% F-15

Aqueous film forming fire extinguishing foam concentrate

Application

STHAMEX-AFFF 1% F-15 is used with all commonly available low expansion foam equipment and installations for fighting fires of class A + B. This, of course includes sub-surface, semi sub-surface and sprinkler systems. Non-aspirating equipment may be used for hydrocarbon fires where the aqueous film is active even without expanded foam. The concentrate is induced at 1 % to water. Sea water, brackish water or treated industrial water does not adversely affect the excellent efficiency of this concentrate.

STHAMEX-AFFF 1% F-15 is typically used in the petrochemical and chemical industry, on airports, Onshore and Offshore, in recycling plants and locations where large fires have to be safely and reliably extinguished within a very short time.

Thanks to its low induction rate **STHAMEX-AFFF 1% F-15** requires only one third of the storage capacity required for foam concentrates designed for 3% induction.

Compatibility with other foaming agents

For immediate usage **STHAMEX-AFFF 1% F-15** can be mixed with any other equivalent foaming agents, independent of the mixing ratio. When **STHAMEX-AFFF 1% F-15** is to be added to stocks of foaming agents we recommend to have the quality of the available stock tested by our laboratory.

Compatibility with other fire extinguishing foams

STHAMEX-AFFF 1% F-15 foam is compatible with all other readily expanded fire extinguishing foams.

Compatibility with powder

STHAMEX-AFFF 1% F-15 is very suitable for the combined use with foam compatible powder.

Storage

STHAMEX-AFFF 1% F-15 can be stored for long periods of time in the sealed original containers and in corrosion-resistant plastic or stainless steel tanks. High temperatures up to +50 °C do not affect the quality; neither does temporary freezing at temperatures below the specified frost resistance limit.

Approval

STHAMEX-AFFF 1% F-15 is an officially approved fire extinguishing agent for low expansion foam applications for class A + B fires.

Approval No.:

PL-13/05

**Head office Hamburg:**

Liebigstraße 5 • 22113 Hamburg/Germany

Tel.: +49 (0)40 73 61 68-0 • Fax: +49 (0)40 73 61 68-60

Sales office Hannover:

Tel.: +49 (0)511 768 358 45

Fax: +49 (0)511 768 358 46

Sales office Jena:

Tel.: +49 (0)3641 635 38 57

Fax: +49 (0)3641 635 38 59

