

# APPARATUS VALVES



HYDRANT

## Hydrant







Available in sizes ranging from 1½" to LDH for portable use (in either aluminum or brass) or permanent mount utilizing the NPT inlet.



APPARATUS VALVES

7-4

Inlet Sizes					Outlet Sizes					Valve Type		Handle Style			Material/Trim				Dimensions		Model	Fig
Female (NPT)		Female (NHT)			Female (NHT)		Male (NHT)			Storz		Ball	Gated	Crank	Hand-wheel	Twist-Lock	Brass			Elk-O-Lite®		
1.5"	2.5"	2.5"	4.0"	5.0"	3.5"	4.0"	4.5"	1.5"	2.5"	3.5"	4.0"						4.5"	4.0"	5.0"		Cast	Satin
		S							S								S	12.5	5.5	X-86A	3	
		S							S								S	6.25	6.4	B-96A	5	
			S	O	O	O	O			O	O	O	S	O				S	12.75	27.5	2940GA	6
S								S							S		O	7.625	4.5	88-1.5	1	
	S								S						S		O	11.625	9.1	88-2.5	1	
		S							S							S	O	12.5	13.75	X-86	2	
		S							S						S		O	8.0	19.75	B-94	4	

<b>Figure 1</b>		<p><b>88</b></p> <ul style="list-style-type: none"> <li>• Non-rising stem design</li> <li>• Metal to metal seat</li> <li>• Pressure rated to 300 psi (20.68 bar)</li> </ul> <p><i>Fig. 1</i></p>	<b>Figure 4</b>		<p><b>B-94</b></p> <ul style="list-style-type: none"> <li>• Adjustable, teflon impregnated, neoprene seat</li> <li>• Pressure rated to 250 psi (17.2 bar)</li> <li>• Red urethane finish with satin brass or chrome trim (<i>specify</i>)</li> </ul> <p><i>Fig. 4</i></p>
<b>Figure 2</b>		<p><b>X-86</b></p> <ul style="list-style-type: none"> <li>• Non-rising stem design</li> <li>• Metal to metal seat</li> <li>• Pressure rated at 175 psi (12.07 bar)</li> <li>• Red urethane finish with satin brass or chrome trim (<i>specify</i>)</li> </ul> <p><i>Fig. 2</i></p>	<b>Figure 5</b>		<p><b>B-96A</b></p> <ul style="list-style-type: none"> <li>• Adjustable, teflon impregnated, neoprene seat</li> <li>• Pressure rated to 200 psi (13.79 bar)</li> </ul> <p><i>Fig. 5</i></p>
<b>Figure 3</b>		<p><b>X-86A</b></p> <ul style="list-style-type: none"> <li>• Non-rising stem</li> <li>• Metal to metal seat</li> <li>• Pressure rated to 175 psi (12.07 bar)</li> </ul> <p><i>Fig. 3</i></p>	<b>Figure 6</b>		<p><b>2940GA</b></p> <ul style="list-style-type: none"> <li>• Acetal ball with UHMWPE seat</li> <li>• Pressure rated to 200 psi (13.79 bar)</li> </ul> <p><i>Fig. 6</i></p>

### ADDITIONAL INFORMATION

#### OTHER PRODUCTS

- Cap and chain are Elkhart model #310 and may be found on page 10-1.

#### THREADS

- Valve information is NHT unless otherwise specified. See index T-12 for alternative thread options.