

liquids

gas

textiles

## 3 kg ABC Dry Powder Fire Rating 13A / 89B FBP3 Manufactured to meet the requirements of BS EN3 and CE Certified Stored pressure - Easy low cost maintenance Safe for use on electrical equipment Suitable for A,B & C class fires Controlled discharge Brass valve - Easy to read pressure gauge Supplied with transport bracket: Powder coated, steel wire complete with stainless steel strap. wood, paper, flammable flammable

Multipurpose Powder Extinguisher ideal for use in vehicles, caravans, boats, agricultural machinery, farms, garages, in the home, offices, and for a wide range of industrial and commercial applications.

Manufacturer's 5 year warranty

Supplied with transport bracket making this product particularly suitable for the commercial vehicle market.

Refilling/Servicing: Should be carried out annually to BS 5306 Part 3, 2009. After complete or partial use the extinguisher should be refilled to BS 6643 Part 1, 1985. Both refilling and servicing to be carried out by a competent person. Spares available on request.

Model	FBP3/CE
Capacity	3 kg
Total Weight	5.1 kg with bracket.
Total Height	400 mm
Total Width (including bracket)	140 mm
Working Temp.	-30° to +60°C
Discharge Time	18 secs
Discharge Range	5 m
Operating Pressure	14 bar @ 20°C
Minimum Burst Pressure	55 bar
Packing Specification	
Qty Per Carton	1
Carton Dimensions	44.5x14x14 cm
Carton Volume	0.009 m <sup>3</sup>
Carton Weight	5.3 kg
Qty Extinguishers per Pallet	128
Pallet Dimensions	120x100x126 cm
Pallet Volume	1.51 m <sup>3</sup>
Pallet Gross Weight	700 kg

