

## Firecom 50 Series Wired FH-51 OVER-HEAD STYLE HEADSET

CONFIGURATION			
	Transmit	Receive	
Intercom	Yes	Yes	
Radio	РТТ	Yes	

The Firecom FH-51 wired headset delivers all the benefits of hands-free, full-duplex communication with your crew. Operating with a stand-alone intercom system or integrated with a mobile radio, the flexible design brings all crew members into constant communication. Broad padded headband remains comfortable for hours of wear. Water-resistant and comfortable ear seals, extended operating temperature, and robust design make this headset ready for action in virtually any fireground environment.



## FIRECOM

7340 SW Durham Rd. | Portland, OR 97224 USA | 800-527-0555 • 503-684-6647 | fax: 503-620-2943 | www.firecom.com



## Keeping firefighters safe, effective & productive

FEATURES		
State-of-the-art ear and hearing protection	Enhanced microphone	
ComLeather over memory foam ear seals for hours of comfortable use	Flexible mic. boom with slide adjustment for accurate/secure positioning	
Enhanced durability and comfort, designed to fit any head size	Microphone boom rotates for left or right dress	
24dB noise reduction rating (NRR)	Noise-cancelling electret microphone ensures optimal clarity	
IP65 rating for dust/water protection when worn	Programmable microphone gain	
Total configurability	Microphone protected by a layer of waterproof material for outdoor use	
Full duplex intercom plus listen-only radio in intercom mode	Microphone muff improves clarity by eliminating wind noise	
Communicates over radio with push-and-hold transmit button	Simple maintenance	
PTT button requires solid push, eliminating accidental transmissions	Black domes for easy cleaning	
Fully programmable to user specifications	Black powder-coated headband for durability	
	Glove-rugged plug for longer life	

SPECIFICATIONS		
Physical	Environmental	
Weight: 19 oz.	IP-65 rated, when worn	
Color: Black	Operating temperature -40 °F (-40 °C) to +158 °F (+70 °C)	
Noise Reduction Rating: 24dB NRR	Storage temperature -40 °F (-40 °C) to +185 °F (+85 °C)	
SAE	Charging Temperature 32 °F (0 °C) to +104 °F (+40 °C)	
Salt Spray per J1455, Sec. 4.3	MIL	
ISO	Humidity per MIL-STD 810F and 810G	
Conducted Transients per 7637-2	Temperature Shock per MIL-STD 810F and 810G	
	Chemical Exposure per MIL-STD 810F and 810G	

Protect your investment for up to five years with ComCare™ Service Programs

Firecom offers unparalleled peace of mind with its exclusive ComCare Service Program. For less than the cost of a single out-of-warranty repair, ComCare Service provides comprehensive support and extends the warranty on your system for up to five years from the date of purchase. The benefits include priority status on technical support, priority repair time and shipping, and discounts up to 50 percent on batteries and non-warranty repairs. ComCare is available for purchase within 90 days of original equipment purchase date. To learn more about the benefits of ComCare, talk to your local dealer, or visit www.firecom.com.



## **FIRECOM**

7340 SW Durham Rd. | Portland, OR 97224 USA | 800-527-0555 • 503-684-6647 | fax: 503-620-2943 | www.firecom.com