

FIREQUIP™



SPECIFICATION SHEET

HI - PRESSURE



FIREQUIP

HIGH PRESSURE BOOSTER HOSE

CONSTRUCTION

- OUTER JACKET IS A TOUGH, DURABLE BLACK RUBBER COVER RESISTANT TO OIL, WEATHER AND ABRASION
- LINER IS A SMOOTH INNER TUBE REINFORCED WITH TWO BRAIDS OF STEEL WIRE
 - COUPLING ARE HYDRAULIC STYLE CRIMPED COATED COUPLINGS
 - ADAPTORS – EASILY ADAPTED FOR NST OR NPSH THREADS

APPLICATIONS

- ATTACK LINE HOSE FOR MULTIPLE PURPOSES
 - INITIAL FRONTLINE ATTACK
 - STRUCTURE FIRE FIGHTING
 - VEHICLE FIRES
 - GRASS, WILDLAND AND FORESTRY FIRES
 - INDUSTRIAL FIRE FIGHTING
- REPLACEMENT HOSE FOR JOHN BEAM HIGH PRESSURE PUMPS

PERFORMANCE FEATURES

- FIRST ATTACK, FULLY LOADED ON REEL
- BLACK OUTER JACKET EASILY MAINTAINED
- SMOOTH INNER TUBER FOR LOW FRICTION LOSS
- WIRE REINFORCEMENT MAINTAINS RIGIDITY UNDER PRESSURE YET REMAINS FLEXIBLE
 - INCREASED SAFETY FACTOR FOR HIGH PRESSURE PUMPS
 - MEETS OR EXCEEDS NFPA STANDARD 1961, CURRENT EDITION
 - FIVE YEAR WARRANTY

FIREQUIP HIGH PRESSURE BOOSTER HOSE PERFORMANCE AND WEIGHT CHART

Hose Size	Working Pressure PSI	Burst Pressure	Weight per 100ft Length (uncoupled)
3/4"	3,000	12,000	53

Website: www.firequip.com • Mailing Address: P.O. Box 2598 Burlington, NC 27216

Toll Free 1-800-334-6823 • Phone: 336-227-0123