



FIREQUIP MAXI-FLEX PVC LIGHTWEIGHT SUCTION ONLY HOSE

CONSTRUCTION

- THE ORIGINAL PVC LIGHTWEIGHT SUCTION ONLY HOSE
- SPECIAL CORRUGATED PVC EXTERIOR FOR MAXIMUM FLEXIBILITY AND SMOOTH WATERWAY
 - CLEAR FLEXIBLE PVC BETWEEN THE HELIX RIBS FOR FULL VISION OF WATER
 - DISTINCTIVE BLACK COLORED HELIX RIBS FOR MAXIMUM UV PROTECTION
- ONCE PIECE EXTRUDED ALUMINUM FIELD REPAIRABLE, REATTACHABLE COLLARS ON COUPLINGS
 - COLLARS ARE ALUMINUM, NOT PLASTIC WHICH IS SUBJECT TO TEMPERATURE EXTREMES

APPLICATIONS

- DRAFTING FROM ANY RURAL OR MUNICIPAL NON-PRESSURIZED WATER SOURCE
 - DESIGNED FOR SUCTION ONLY!
- PVC HOSE SHALL NOT BE USED ON PRESSURIZED HYDRANTS OR FOR RELAY PUMPING. THIS IS NOT A SUPPLY HOSE FOR HYDRANT USE.
 - LIMITED EXPOSURE TO DIRECT SUNLIGHT FOR LONG PERIODS OF TIME.

PERFORMANCE FEATURES

- ULTRA FLEXIBLE AND LIGHTWEIGHT, ONE-MAN HOOK-UP OPERATION IF NECESSARY
 - DESIGNED FOR FULL VACUUM
 - NO PLASTIC COUPLINGS
 - CLEAR HOSE FOR FULL VISION OF WATER FLOW
- TIME SAVING WITH LESS MANPOWER REQUIRED COMPARED TO CONVENTIONAL SUCTION HOSE
- 4", 4.5", 5" AND 6" COUPLED WITH REATTACHABLE BOLT-ON COUPLINGS (FOLDING LONG HANDLES AVAILABLE)
 - MEETS OR EXCEEDS NFPA STANDARD 1961, CURRENT EDITION
 - FIVE YEAR WARRANTY
- 3" COUPLED WITH EXPANSION RINGS, REATTACHABLE COUPLINGS AVAILABLE

FIREQUIP MAXIFLEX PERFORMANCE AND WEIGHT CHART

Hose Size	Working Pressure psi 68 degrees F	Working Pressure psi 104 degrees F	Weight per 10ft Length (uncoupled)
3"	45	25	12
4"	35	18	20
4.5"	35	18	25
5"	35	18	25
6"	30	15	38

Website: www.firequip.com • Mailing Address: P.O. Box 2598 Burlington, NC 27216

Toll Free 1-800-334-6823 • Phone: 336-227-0123