



FIREQUIP REEL LITE BOOSTER LIGHTWEIGHT WOVEN TPU FORESTRY REEL HOSE

SPECIFICATIONS

1. SCOPE:

This specification covers the construction and performance criteria for Reel-Lite Booster hose suitable for a proof test pressure of 800 PSIG.

2. JACKET CONSTRUCTION:

- a.) The hose shall be of a single jacket construction.
- b.) The jacket shall be made with virgin spun polyester warp yarn woven in a twill weave and it shall be treated with yellow or red Wear Guard treatment.

3. LINING:

- a.) The hose shall be polyurethane lined and the lining material shall be suitable for potable water (when so ordered).

4. HYDROSTATIC PRESSURE TESTS:

- a.) The hose shall have a service temperature range of -60° F to 140° F.
- b.) The hose shall have a minimum service test pressure of 400 PSIG.
- c.) The hose shall have a minimum proof test pressure of 800 PSIG.
- d.) The hose shall have a minimum burst pressure of 2000 PSIG.
- e.) The hose shall have a kink radius of no greater than 4.5" and a kink diameter no less than 9".

5. DIMENSIONS:

- a.) The hose shall not weigh more than 20 lbs. per 100' uncoupled.
- b.) The coil diameter on a standard 10" REEL (100') is 18 inches.

6. COUPLINGS:

The hose shall be coupled with hardcoat aluminum expansion ring couplings.
Field repairable couplings available.

7. QUALITY ASSURANCE PROVISIONS:

- a.) Inspection: Purchasing Agent shall reserve the right to visit the manufacturing plant during each phase of the production operations. Hose construction, lining and cover properties, safety factors and performance characteristics will all be taken into consideration, insuring that the hose to be supplied is made exactly to these specifications.
- b.) Quality Standard: Hose is designed and tested to meet NFPA 1961 (current edition) Standards on Fire Hose. The fire hose furnished under the terms of this proposal has a potential service life of ten years, barring mistreatment or accidental damage that would render the hose unfit for service.

8. WARRANTY:

The manufacturer warrants the hose to be free from defects in materials and workmanship for a period of one year. This warranty shall provide for the repair or replacement of hose and couplings proven to have failed due to faulty material or workmanship.

CONSTRUCTION

- ***Single Jacket**-100% High Tenacity Polyester Cover
- ***Circular Woven with Helical Inner Reinforcement**
- ***Polyurethane Liner**
- ***Expansion Ring Couplings or Field Repairable Couplings**
- ***Protective Treated Color**-Wear Guard, Yellow or Red

APPLICATIONS

- ***First Arrival Frontline Attack Line**
- ***Grass and Brush Fires**
- ***Wildland Fires**
- ***Dumpster Fires**
- ***Industrial Use**

PERFORMANCE FEATURES

- ***Lightweight**
- ***Flexible with Helix Reinforcement**
- ***Low Drag Resistance**
- ***Fully Loaded, Ready on Reel**
- ***TPU Liner Has Low Kink Resistance**

FIREQUIP REEL-LITE PERFORMANCE AND WEIGHT CHART

Hose Size	Coupling Bowl Size	Proof Test Pressure (psi)	Service Test Pressure (psi)	Burst Test Pressure (psi)	Weight per 50ft Length (uncoupled)	Weight per 100ft Length (uncoupled)
1"	1-3/16"	600	300	900	10 lbs	20 lbs

Website: www.firequip.com • Mailing Address: P.O. Box 2598 Burlington, NC 27216

Toll Free 1-800-334-6823 • Phone: 336-227-0123