

GUIDIR® IR518

Affordable Monocular Handheld Thermal Imager

With newly adopted thermal vision technology, IR518 series set a new standard for small, light weight thermal imaging cameras. Compact design and hand-sized structure allows for easy carrying and operation. Thermal image and video storage function helps you to store the detection process as an evidence for review. The perfect hermetic structure and encapsulation realize overall protects for IR518 series and makes them perfect for public safety, police office and security operations.

Features and Benefits



IR video recording

IR video recording All evidence of crime can be saved and checked for future use

SD card storage

Allows storing thermal images and video clips



Rugged and Portable design

Pocket-size and IP67 compact design, goeverywhere use in all circumstances.

Different Versions Available

3 different versions, multichoice for different detection requirements



Applications

- Search and rescue
- Security monitoring
- Portable law enforcement
- Border security
- Routine patrols



Specifications

Detector			
Detector material	Uncooled FPA microbolometer		
Spectral Range	8-14 µ m		
Pitch	25 µ m		
Pixels	384 x 288 / 160 x 120		
NETD	≤100mk@25 ℃ / ≤120mk@2	25°C	
Optics			
Lens	50mm/F1.1 25mm/F1.0		
FOV	384X288 detector	160X120 detector	
	10.97" ×8.24" (50mm)	4.58 X3.44 (50mm)	
	21.74° X16.39° (25mm)	9.15 X6.87 (25mm)	
Image Storage			
Туре	2GB SD card (4GB SD card optional)		
File Format	JPG	JPG	
Image Presentation			
Display	OLED viewfinder	OLED viewfinder	
	852×600 Pixels	852×600 Pixels	
	256 level gray	256 level gray	
Video Output	PAL		
Frame Frequency	50Hz		
Electronic Zoom	×2		
Adjust	Auto/Semi-auto/Manual brightness/Contrast adjustment		
Polarity	Black/White hot		
Power System			
AC/DC adapter	110-240VAC/9VDC		
Rechargeable Li-ion	4AA Lithium 4.8VDC		
Camcorder battery			
Power dissipation	<4W		
Battery Operating Time	>2hr		
Interfaces			
Interfaces	Analog video output / USB port/ RS232		
Environmental Specifica	tion		
Operating Temperature	-20 C - +50 C (-40 C - +60 C optional)		
Storage Temperature	-40℃ -+60℃		
Encapsulation	IP67		
Physical Characteristics			
Color	Black		
Weight	0.5kg (without batteries)		
Size	182mmx97mmx68mm		



Address: No. 26 Shucheng Rd., Wuhan, P.R. China Zip Code: 430070 Tdi: 027-87671925 / 87671991 / 87671983 Fax: 027-87671927 E-mail: overseas@guide-infrared.com Webste: www.guide-infrared.com