

## Exit Sign Frames

### Features:

- ▶ Complies with BS5266 for open areas
- ▶ Supports 2 lighting lines with 127 points per line
- ▶ Slim profile - only 100 mm deep
- ▶ Robust design



### Description

20 & 40m Emergency Exit Sign Frame (battery required). The cup features a bi-coloured status LED indicating charge/fault status (green for charging, red for fault). The frames require an exit sign lens ([sold separately - see below](#)).

Specification		
Cup and bar colour	White	
Materials	Fire resistant PC + ABS plastic	
Fire class	UL94 V-0	
Operation time	1 hour / 3 hour	
Dimensions of frame (mm)	EL-20(WHT) 200W x 125H x 100D (inc cup) EL-40(WHT) 330W x 125H X 100D (inc cup)	
Weight (g)	EL-20(WHT) 150g EL-40(WHT) 212g	
Compatible lenses	EL-20G-D(ISO) EL-20G-L(ISO) EL-20G-R(ISO) EL-20G-U(ISO) EL-40G-D(ISO) EL-40G-L(ISO) EL-40G-R(ISO)	EL-40G-U(ISO) EL-20G-D EL-20G-L EL-20G-R EL-40G-D EL-40G-L EL-40G-R
Operating Voltage		
Current Consumption (Charger set for 3h standby time [mA])		
3.3	0	
6.5	1	
7.0	2	
8.5	3	
10.0	4	

## Exit Sign Frames

Specification	
14.0	5
24.0	6
34.0	7
Sleep mode	1 mA

### Order Codes

#### Product

20m Emergency exit sign frame  
40m Emergency exit sign frame

#### Part Number

EL-20(WHT)  
EL-40(WHT)