

# GCT 5114 EVO 3 | Combi Tool

Specifications	
article number	151.000.521
model	GCT 5114 EVO 3
short description	Combi Tool
max. working pressure	psi 10443
battery included	no
max. cutting opening	in 10.9
max. spreading force	lbf 303492
spreading distance	in 14.3
min. spreading force (EN 13204)	lbf 7419
theoretical calculated spreading force	lbf 166359
theoretical cutting force	lbf 60249
max. squeezing force	lbf 7644
protection rate	IP54
sound emission @ 1m/3.25ft	dB(A) 74
sound emission @ 4m/13ft	dB(A) 65
hydraulic oil type	ISO-L HV VG 15/22
weight, ready for use	lb 31.1
weight excl. battery	lb 28.9
temperature range	°F -4 + 131
dimensions (AxBxC)	in 28.9 x 11 x 8.1
EN 13204 classification	BK33/362-E-14.1
EN 13204, cutting capacity	1E 2E 3E 4E 5E
NFPA 1936 compliant	yes
NFPA 1936, cutting capacity	A5 B5 C5 D6 E4 F3
NFPA 1936, HSF	lbf 8992
NFPA 1936, LSF	lbf 6744

Safety factors / tests	
hydraulic safety factor	2:1
endurance test tool	1000 cycles of spreading while the tool is loaded and 1000 cycles of biting in material that cannot be cut
endurance test dead man's handle	6000 cycles

Standard supplied with	
<ul style="list-style-type: none"> <li>Carrying handle with integrated LED lighting</li> <li>i-Bolt Technology</li> </ul>	

Required articles	
Greenline Battery BPA286	151.000.307
Greenline Battery Charger BCH2	150.182.209
Greenline Battery BPA285	150.006.208
Greenline Battery Charger BCH3	150.182.286
Greenline Battery Charger BCH1	150.182.208

