

E³Point[®] SPECIFICATIONS

Toxic and Combustible Gas Detector Network Platform (BACnet MS-TP, Modbus)



General Specifications					
Uses	Wall or duct-mounted, BAS or controller networkable gas detector for monitoring carbon monoxide (CO), nitrogen dioxide (NO ₂), hydrogen sulfide (H ₂ S), oxygen (O ₂), methane (CH ₄), hydrogen (H ₂) and propane (C ₃ H ₈). (Note: E³Point network version replaces Vulcain model VA201T)				
Size	20.56 x 14.90 x 6.72cm (8.09 x 5.87 x 2.65") (H x W x D)				
Power Requirement	24 Vac nominal (17-27Vac), 50/60 Hz, 0.35 A; 24 Vdc nominal (20-38Vdc)				
Relay Output	1 DPDT relay, 5A @ 250Vac; 5A @ 30Vdc				
Communications	RS485 Modbus; BACnet MS-TP master				
Operating Environment	Commercial, Indoor, Extreme Temperature Environments				
Operating Temperature	H ₂ S, NO ₂ , O ₂ , CH ₄ , H ₂ , C ₃ H ₈ : -40 to 50°C (-40 to 122°F) CO: -20 to 50°C (-4 to 122°F); future available CO version: -40 to 50°C (-40 to 122°F)				
Display	8 character, 2 line backlit LCD				
Visual Indicators	Green LED: Power Amber LED 1: Alarm/Fault Amber LED 2: Alarm/Fault				
Audible Alarm	>85 dBA at 3 m (10 ft)				
Accuracy	+/- 3% of full scale @ 25 C				
Gases Detected, Detection Ranges and Alarm Levels					
Gas	Resolution	Range	Alarm A	Alarm B	Alarm C
CO (Carbon monoxide)	1 ppm	0-250 ppm	25 ppm	100 ppm	225 ppm
H₂S (Hydrogen sulfide)	0.1 ppm	0-50 ppm	10 ppm	15 ppm	20 ppm
NO₂ (Nitrogen dioxide)	0.1 ppm	0-10 ppm	0.7 ppm	2 ppm	9 ppm
O₂ (Oxygen)	0.1% vol.	0-25% vol.	19.5% vol.	22% vol.	22.5% vol.
H₂ (Hydrogen)	0.5% LEL	0-100% LEL	25% LEL	50% LEL	90% LEL
CH₄ (Methane)	0.5% LEL	0-100% LEL	25% LEL	50% LEL	90% LEL
C₃H₈ (Propane)	0.5% LEL	0-100% LEL	25% LEL	50% LEL	90% LEL
Enclosure					
	Polycarbonate				
Certification					
	CSA C22.2 No. 61010-1, UL 61010-1; FCC part 15; ICES-003 issue 4; ISO 9001-2008				

ORDERING INFORMATION

Single-Gas, Surface-Mount

** Base unit and sensor cartridge sold together ** Base unit only; sensor cartridge sold separately*

Part Number	Description
E3SBSCO*	E ³ Point, CO, Surface-mount, BACnet MS-TP, 24Vac/dc, -20 to 50°C (-4 to 122°F)
E3SB**	E ³ Point, Surface-mount, BACnet MS-TP, 24Vac/dc, -40 to 50°C (-40 to 122°F)
E3SMSCO*	E ³ Point, CO, Surface-mount, Modbus, 24Vac/dc, -20 to 50°C (-4 to 122°F)
E3SM**	E ³ Point, Surface-mount, Modbus, 24Vac/dc, -40 to 50°C (-40 to 122°F)

Duct-Mount

Part Number	Description
E3DBSCO*	E ³ Point, CO, Duct-mount, BACnet MS-TP, 24Vac/dc, -20 to 50°C (-4 to 122°F)
E3DB**	E ³ Point, Duct-mount, BACnet MS-TP, 24Vac/dc, -40 to 50°C (-40 to 122°F)
E3DMSCO*	E ³ Point, CO, Duct-mount, Modbus, 24Vac/dc, -20 to 50°C (-4 to 122°F)
E3DM**	E ³ Point, Duct-mount, Modbus, 24Vac/dc, -40 to 50°C (-40 to 122°F)

Sensor Cartridges

Part Number	Description
E3SCO	CO Cartridge -20 to 50°C (-4 to 122°F), Carbon Monoxide
E3NO2	NO ₂ Cartridge -40 to 50°C (-40 to 122°F), Nitrogen Dioxide
E3H2S	H ₂ S Cartridge -40 to 50°C (-40 to 122°F), Hydrogen Sulfide
E3H2	H ₂ Cartridge -40 to 50°C (-40 to 122°F), Hydrogen
E3O2	O ₂ Cartridge -40 to 50°C (-40 to 122°F), Oxygen
E3M	CH ₄ Cartridge -40 to 50°C (-40 to 122°F), Methane
E3P	C ₃ H ₈ Cartridge -40 to 50°C (-40 to 122°F), Propane

EXAMPLES OF HOW TO ORDER

To order a network version, surface-mount, BACnet MS-TP, CO detector, -20 to 50°C (-4 to 122°F): Order E3SBSCO

To order a network version, surface-mount, Modbus, H₂S detector, -40 to 50°C (-40 to 122°F): Order E3SM + E3H2S

To order a network version, duct-mount, BACnet MS-TP, NO₂ detector, -40 to 50°C (-40 to 122°F): Order E3DB + E3NO2

Find out more

www.honeywellanalytics.com

Toll free: 1 800 563 2967

Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.

Honeywell