

NORTH CONTROLLED ENVIRONMENT GLOVES

NITRILE

NORTH- NITRI-BOX™ GLOVE BOX GLOVES

Last Updated – (May 2013)



GENERAL INFORMATION		DIMENSIONS	
Base Material	Nitrile	Cuff Style	Rolled Bead
Material Color	Green	Bead Diameter:	3.2 to 6.4mm (0.125 to 0.25in)
Surface Finish	Smooth	Standard Lengths	32in (+/- 1in)
Country of Origin	China	Film Thickness 18mil	0.41 to 0.56 mm (0.016 to 0.022 in)
Case Pack	5 prs/bag, 10 prs/case		

AVAILABLE HAND SIZES	
Port Diameter, inches	Ambidextrous
8	9Q
10	10H

PRODUCT FEATURES

- Broad range of resistance against acids, bases, alcohols, esters, and other solvents.
- Mechanically robust with high abrasion, puncture, cut and snag resistance, providing for long glove service life.
- Soft, flexible feel for reduced hand fatigue.
- Compatible with alcohol cleaning practices; will not degrade or become slippery.
- Textured grip is safer for handling both wet and dry objects.
- Inherently anti-static, providing a safer working environment where electrostatic buildup is a concern.
- Complies with USDA and FDA regulations, 21 CFR, for use in food processing.

APPLICATIONS



Glove box operations in the pharmaceutical, biotechnical, semi-conductor, nuclear, defense, and manufacturing industries.

NORTH® HAND PROTECTION – Technical Data Sheet

CERTIFICATIONS / STANDARDS

OSHA Standard - 29 CFR 1915.157 The employer shall ensure that each affected employee uses appropriate hand protection and other protective clothing where there is exposure to hazards such as skin absorption of harmful substances, severe cuts or lacerations, severe abrasions, punctures, chemical burns, thermal burns, harmful temperature extremes, and sharp objects.

Complies with

	TEST METHOD	LEVEL	TEST RESULT
CE Certified EN420, EN388  4 1 0 2	EN388:2003		
	Abrasion	4	≥ 8,000 cycles
	Cut	1	≥ 1,2 index
	Tear	0	< 10 newtons
	Puncture	2	≥ 60 newtons
CE Certified EN374  JKL	EN374-1:2003		Breakthrough Time
	n-Heptane	6	> 8 hrs
	Sodium Hydroxide (40%)	6	> 8 hrs
	Sulfuric Acid (96%)	4	> 2 hrs
	EN374-2:2003		
	Resistance to Penetration	3	(Inspection level G1, AQL ≤ 0.65)
Physical Properties according to ASTM D412	Tensile Strength		31 Mpa (4500 psi) min
	Ultimate Elongation		450% min
	300% Tension Stress		15 Mpa (2200 psi) max

LAUNDERING / STORAGE

Chemical resistant gloves are not designed for laundering.

Three year shelf life when stored in original packaging in a cool dry place away from light. Recommended temperature range: 50°F to 86°F (10°C to 30°C).

GLOVE BOX PART NUMBERING

8	LA	18	32	A	/9Q
Port diameter (in)	Material LA = Nitrile	Nominal thickness (mil)	Nominal length (in)	Hand specificity A = ambidextrous No letter = RH/LH pr	Size (9 ¾)

WARRANTY

Honeywell products are covered by and subject to the terms of the Honeywell Safety Products Limited Warranty that is printed in our published price list. The Honeywell Safety Products Limited Warranty is the only written warranty of any force and effect, and all other written warranties are disclaimed in their entirety. In no event shall Honeywell Safety Products or any of its authorized dealers be liable for any damages in excess of the purchase price of the relevant product. This limitation applies to damages of any kind, including but not limited to direct or indirect damages or other special, incidental exemplary or consequential damages, whether arising out of the use or inability to use the product, even if we or any of our authorized dealers has been advised of the possibility of the damages or any claim by any other party. Servicing of any product with parts not approved by us will void the warranty and may result in loss of any certification or approval applicable to the product.



WARNINGS

*Extreme caution should be used around moving machinery.

**Cleaning gloves that have been in contact with toxic or corrosive chemicals may result in a chemical reaction, including fumes that could cause personal injury, serious illness, or death.

Honeywell Safety Products
900 Douglas Pike
Smithfield, RI 02917
Tel: 800.430.5490

Canada
Tel: 1.888.212.7233

www.honeywellsafety.com