


# Portable Hydraulic Hose Reels



MADE IN FRANCE



▼ Single 1 DH and Double 2 DH Hydraulic Hose reels




2DH 20 P

Hydraulic hoses  
and hoses reels  
for supplying  
**HYDR'AM**<sup>®</sup>  
tools.

## DESCRIPTION

- Single or double reels fitted with paired thermoplastic hoses. Black for supply and red or blue for the return, with spring loaded end protectors.
- Hoses fitted with HP quick action anti-pollution male/female couplers with automatic locking and protective stoppers.
- Relief valve on coupler end
- Hose operating pressure 700 bar
- Hose bursting pressure 2800 bar, safety coefficient: 4/1
- Rotary seal 700 bar
- Blocking system for hub and hose guide
- Anodised aluminium flanges
- Manual rewind
- Single chassis (1 DH) or double (2 DH) or on hydraulic unit chassis. Lateral (F) or front (T) mounting
- Exists also with a length of 10 meters



1DH 20 P

## CHARACTERISTICS

Model	1 DH 15P	1 DH 20P	1DH 25P	2 DH 15P	2 DH 20P	2 DH 25P
Operating pressure	700 bar	700 bar	700 bar	700 bar	700 bar	700 bar
Hydraulic fluid	Total ZS 32	Total ZS 32	Total ZS 32	Total ZS 32	Total ZS 32	Total ZS 32
Dimensions	462x262x562	462x262x562	462x262x562	540x380x545	540x380x545	540x380x545
Weight (portable)	18 kg	20 kg	22 kg	30,6 kg	34,6 kg	38,6 kg

Powerful, Lightweight and Reliable in Rescue Operations