



## SHELVING UNITS FOR WATER-ENDANGERING SUBSTANCES IN SMALL CONTAINERS

### For the storage of water-endangering substances

- ◆ With sump tray shelves at each storage level
- ◆ 2 different combinable shelf widths (1000 and 1300 mm) allow optimal utilisation of existing storage space
- ◆ Mixture of basic and extension units allows extension as required

### Fittings:

- ◆ All shelving parts and sump tray shelves galvanized
- ◆ Height-adjustable shelves at intervals of 25 mm
- ◆ Max. load per storage level 200 kg with uniformly distributed load
- ◆ Max. unit load 1200 kg
- ◆ Stable construction by reinforced struts
- ◆ Dismounted delivery for easy self-assembly



KG-GR 100 W, Article No. R71-2101-D



Environmental cabinets can be found on page 78 !



KG-GR 130 W, basic unit, Article No. R71-2103-D and KG-GR 100 W, extension unit, Article No. R71-2102-D

Model	KG-GR 100 W	KG-GR 130 W
External dimensions W x D x H (mm)	1060 x 635 x 2000	1360 x 635 x 2000
Lowest storage level fittings	1 x base sump tray, galvanized	1 x base sump tray, galvanized
Other storage level fittings	4 x sump tray shelves, galvanized	4 x sump tray shelves, galvanized
Sump capacity (l)	5 x 30	5 x 35
Article No., basic unit	R71-2101-D	R71-2103-D
External dimensions, extension unit W x D x H (mm)	1010 x 635 x 2000	1310 x 635 x 2000
Article No., extension unit	R71-2102-D	R71-2104-D
Accessory	Article No.	Article No.
Additional sump tray shelf as storage level	R71-2108-D	R71-2109-D



## SHELVING UNITS FOR FLAMMABLE LIQUIDS IN SMALL CONTAINERS

### For the storage of flammable liquids

- ◆ With 1 x sump tray shelf as lowest storage level and 4 x galvanized grid-type shelves
- ◆ 2 different combinable shelf widths (1000 and 1300 mm) allow optimal utilisation of existing storage space
- ◆ Mixture of basic and extension units allows extension as required

### Fittings:

- ◆ All shelving parts, sump tray shelves and grid-type shelves galvanized
- ◆ Height-adjustable shelves at intervals of 25 mm
- ◆ Max. load per storage level 200 kg with uniformly distributed load
- ◆ Max. unit load 1200 kg
- ◆ Stable construction by reinforced struts
- ◆ Dismounted delivery for easy self-assembly



Our standard - 5 storage levels!

KG-GR 100 G, basic unit, Art. No. R71-2110-D and extension unit, Art. No. R71-2111-D



Our standard - 5 storage levels!

KG-GR 100 G, Article No. R71-2110-D



Hazardous substances cabinets can be found from page 111 !

Model	KG-GR 100 G	KG-GR 130 G
External dimensions W x D x H (mm)	1060 x 635 x 2000	1360 x 635 x 2000
Lowest storage level fittings	1 x base sump tray, galvanized	1 x base sump tray, galvanized
Other storage level fittings	4 x grid shelves, galvanized	4 x grid shelves, galvanized
Sump capacity (l)	1 x 30	1 x 35
Article No., basic unit	R71-2110-D	R71-2112-D
External dimensions, extension unit W x D x H (mm)	1010 x 635 x 2000	1310 x 635 x 2000
Article No., extension unit	R71-2111-D	R71-2113-D
Accessory	Article No.	Article No.
Additional grid shelf as storage level	R71-2118-D	R71-2119-D



## SHELVING UNITS FOR WATER-ENDANGERING AND AGGRESSIVE LIQUIDS IN SMALL CONTAINERS

### For the storage of water-endangering and aggressive liquids

- ◆ With PE sump tray shelves at each storage level
- ◆ 2 different combinable shelf widths (1000 and 1300 mm) allow optimal utilisation of existing storage space
- ◆ Mixture of basic and extension units allows extension as required



**Our standard - 5 storage levels!**

KG-GR 130 WPE, basic unit, Art. No. R71-2122-D and extension unit, Art. No. R71-2123-D



### Fittings:

- ◆ All shelving parts galvanized
- ◆ Sump tray shelves with PE insert
- ◆ Height-adjustable shelves at intervals of 25 mm
- ◆ Max. load per storage level 200 kg with uniformly distributed load
- ◆ Max. unit load 1200 kg
- ◆ Stable construction by reinforced struts
- ◆ Dismounted delivery for easy self-assembly



**Acid and alkali cabinets can be found on page 91 !**

Model	KG-GR 100 WPE	KG-GR 130 WPE
External dimensions W x D x H (mm)	1060 x 635 x 2000	1360 x 635 x 2000
Lowest storage level fittings	1 x PE base sump tray	1 x PE base sump tray
Other storage level fittings	4 x PE sump tray shelves	4 x PE sump tray shelves
Sump capacity (l)	5 x 30	5 x 35
Article No., basic unit	R71-2120-D	R71-2122-D
External dimensions, extension unit W x D x H (mm)	1010 x 635 x 2000	1310 x 635 x 2000
Article No., extension unit	R71-2121-D	R71-2123-D
<b>Accessory</b>	<b>Article No.</b>	<b>Article No.</b>
Additional PE sump tray shelf as storage level	R71-2128-D	R71-2129-D



## SHELVING UNITS FOR WATER-ENDANGERING AND AGGRESSIVE LIQUIDS IN SMALL CONTAINERS

### For the storage of water-endangering and aggressive liquids

- ◆ With 1 x PE sump tray shelf as lowest storage level and 4 x galvanized or PE grid shelves
- ◆ 2 different combinable shelf widths (1000 and 1300 mm) allow optimal utilisation of existing storage space
- ◆ Mixture of basic and extension units allows extension as required



Our standard - 5 storage levels!

KG-GR 130 GPE, basic unit, Art. No. R71-2132-D and KG-GR 130 PG, extension unit, Art. No. R71-2143-D



### Fittings:

- ◆ All shelving parts galvanized
- ◆ Tray-shaped shelves with PE insert
- ◆ 4 x galvanized or PE grid shelves
- ◆ Height-adjustable shelves at intervals of 25 mm
- ◆ Max. load per storage level with uniformly distributed load: with galvanized grid shelf 200 kg, with PE grid shelf 130 kg
- ◆ Max. unit load 1200 kg
- ◆ Stable construction by reinforced struts
- ◆ Dismounted delivery for easy self-assembly



PE environmental cabinets can be found on page 48!

Model	KG-GR 100 GPE	KG-GR 130 GPE	KG-GR 100 PG	KG-GR 130 PG
External dimensions W x D x H (mm)	1060 x 635 x 2000	1360 x 635 x 2000	1060 x 635 x 2000	1360 x 635 x 2000
Lowest storage level fittings	1 x PE base sump tray	1 x PE base sump tray	1 x PE base sump tray	1 x PE base sump tray
Other storage level fittings	4 x galvanized grid shelves	4 x galvanized grid shelves	4 x PE grid shelves	4 x PE grid shelves
Sump capacity (l)	1 x 30	1 x 35	1 x 30	1 x 35
Article No., basic unit	R71-2130-D	R71-2132-D	R71-2140-D	R71-2142-D
External dimensions, extension unit W x D x H (mm)	1010 x 635 x 2000	1310 x 635 x 2000	1010 x 635 x 2000	1310 x 635 x 2000
Article No., extension unit	R71-2131-D	R71-2133-D	R71-2141-D	R71-2143-D

Accessory	Article No., galvanized grid shelf		Article No., PE grid shelf	
Additional shelf as storage level	R71-2118-D	R71-2119-D	R71-2148-D	R71-2149-D



## FOR THE STORAGE OF HAZARDOUS SUBSTANCES IN SMALL CONTAINERS

Our hazardous substances shelving units on pages 54 - 57 can be supplied in many different version:

- ◆ Powder-coated support profiles
- ◆ Various shelving heights (e.g. 2500 mm)
- ◆ Various shelving widths (e.g. 700 mm)
- ◆ Various shelving depths (e.g. 400, 500 or 800 mm)
- ◆ Sump tray shelves with higher sump capacity
- ◆ Various base sump tray sizes



We can supply „Your hazardous substances shelving“ according to your particular space requirements. Please make use of our planning service!

### Combinability:

All the hazardous substances shelving units on pages 54 - 57 and 62 can be combined at will. This means that the available storage space can be equipped with shelving that exactly matches the substances to be stored with respect to container sizes and amounts of substances. The modular construction with basic and extension units means that the hazardous substances shelving can be extended at any time.





## STAINLESS STEEL SHELVING UNITS FOR WATER-ENDANGERING AND AGGRESSIVE LIQUIDS IN SMALL CONTAINERS

For the storage of water-endangering and aggressive liquids in small containers

- ◆ Especially suitable for use in laboratory, hospital and food sector
- ◆ Available in 2 different shelf depths (300 + 500 mm)
- ◆ Quick and easy installation

### Fittings:

- ◆ All shelving parts and base sump tray made from stainless steel 1.4301
- ◆ Height-adjustable slotted shelves at intervals of 150 mm
- ◆ Adjustable feet on the bottom of the shelf stands
- ◆ Max. field load 1000 kg
- ◆ Basic unit includes 2 x shelf stands, 3 x slotted shelves, 1 x base sump tray, 1 x cross bracing
- ◆ Extension unit includes 1 x shelf stands, 3 x slotted shelves, 1 x base sump tray



KG-GR 1200-500 VA, basic unit, Art. No. R71-3024-A and KG-GR 1000-500 VA, extension unit, Art. No. R71-3023-A



KG-GR 1200-300 VA, basic unit, Art. No. R71-3014-A



KG-GR 900-300 VA, basic unit, Art. No. R71-3012-A

Model	KG-GR 600-300 VA	KG-GR 900-300 VA	KG-GR 1200-300 VA	KG-GR 900-500 VA	KG-GR 1000-500 VA	KG-GR 1200-500 VA
External dimensions W x D x H (mm)	600 x 300 x 1800	900 x 300 x 1800	1200 x 300 x 1800	900 x 500 x 1800	1000 x 500 x 1800	1200 x 500 x 1800
Sump capacity (l)	20	30	40	30	35	40
Max. field load (kg)	150	150	100	150	150	100
Article No., basic unit	R71-3010-A	R71-3012-A	R71-3014-A	R71-3020-A	R71-3022-A	R71-3024-A
Article No., extension unit	R71-3011-A	R71-3013-A	R71-3015-A	R71-3021-A	R71-3023-A	R71-3025-A

Accessory	Article No.	Article No.	Article No.	Article No.	Article No.	Article No.
Additional slotted shelf	R71-3030-A	R71-3031-A	R71-3032-A	R71-3033-A	R71-3034-A	R71-3035-A
Cross bracing for extension unit*	R71-3040-A	R71-3041-A	R71-3042-A	R71-3041-A	R71-3044-A	R71-3042-A

\* In 3 shelf areas of each a cross bracing is to be installed



## HAZARDOUS SUBSTANCES SHELVING UNITS FOR SMALL CONTAINERS WITH SUMP PALLET

- ◆ Large sump capacity by combination of sump pallet and hazardous substances shelving
- ◆ Galvanized grid shelves
- ◆ Dismounted delivery with instructions for easy self-assembly
- ◆ Approved sump pallet with Ü-sign

### Shelf fittings:

- ◆ Galvanized
- ◆ Height-adjustable shelves at intervals of 25 mm
- ◆ Max. load per storage level 200 kg\*

### Sump pallet fittings:

- ◆ Painted in RAL 5015 - sky blue or fire-galvanized, dimensions please see table below
- ◆ Sump capacity 210 liters
- ◆ Safe liquid transfer with projecting grid in front of shelves
- ◆ Ground clearance 100 mm



GR1-G, sump pallet painted, Art. No. R71-2061-C

\* with uniformly distributed load



GR2-G, sump pallet painted, Art. No. R71-2081-C



GR1-G, sump pallet fire-galvanized, Art. No. R71-1061-C



GR2-G, sump pallet fire-galvanized, Art. No. R71-1081-C



Ideally suitable for storing agricultural pesticides!

Model	GR1-G	GR2-G	GR3-G
Dimensions W x D x H (mm)	1060 x 635 x 2100	2085 x 635 x 2100	3095 x 635 x 2100
Sump pallet dimensions W x D x H (mm)	1250 x 820 x 340	2420 x 820 x 240	3200 x 820 x 215
Fittings	5 x grid shelves	2 x 5 grid shelves	3 x 5 grid shelves
Sump capacity (l)	210	210	210
Article No., sump pallet painted	R71-2061-C	R71-2081-C	R71-2091-C
Article No., sump pallet <u>fire-galvanized</u>	R71-1061-C	R71-1081-C	R71-1091-C



## HAZARDOUS SUBSTANCES SHELVING UNITS FOR SMALL CONTAINERS WITH SUMP PALLET



GR3-G, sump pallet painted, Article No. R71-2091-C

Hazardous substances shelvings are available in several versions:

- ◆ Various shelving heights
- ◆ Various shelving widths
- ◆ Various shelving depths
- ◆ Various sump pallet sizes



We are pleased to meet your areal specifications. Take advantage of our planning service !

