



SIS TYPE 30 / 600 GL AND SIS TYPE 30 / 1200 GL

Approved for storage of flammable liquids at the workplace as per EN 14470-1 (type 30) and TRbF 20 - L

- ◆ Whole construction tested and approved by an authorized materials testing institute as per EN 14470-1 (type 30) with a fire resistance >30 minutes
- ◆ Body made from B1 material RAL 7035 - light grey, door(s) either in RAL 7035 - light grey or RAL 1007 - daffodil yellow and fire safety glass
- ◆ Height-adjustable shelves at intervals of 32 mm
- ◆ Automatic thermal closing mechanism if fire occurs
 - Door(s) after temperature increase to $\leq 50^{\circ}\text{C}$ and
 - Inlet and outlet channels after temperature increase to 70°C ($\pm 10^{\circ}\text{C}$)
- ◆ DN 80 ventilation connection for exhaust air extraction on cabinet roof
- ◆ Operation complies with TRbF 20-L (approved even without exhaust air connection!)
- ◆ Ground connection in accordance with BGR 132 (avoidance of sources of ignition)
- ◆ Markings according to EN 14470-1 / TRbF 20, Annex L / ISO 3864
- ◆ Leveling feet for installing cabinet horizontally
- ◆ Door(s) with cylinder lock
- ◆ For model 600 single door hinged right as standard



Sis Type 30 / 1200 GL, Article No. B80-2656-A, door RAL 7035 - light grey, incl. 3 shelves, base sump tray and perforated cover plate



Sis Type 30 / 600 GL, Art. No. B80-2655-A, door RAL 1007 - daffodil yellow, incl. 3 shelves, base sump tray and perforated cover plate



Sis Type 30 / 600 GL, Art. No. B80-2654-A, door RAL 7035 - light grey, incl. 3 shelves, base sump tray and perforated cover plate

With inner fittings:

- ◆ 1 x base sump tray (sump capacity model 600 = 23 liters and model 1200 = 33 liters)
- ◆ 1 x perforated base tray cover as 1st storing level
- ◆ 3 x shelves
- ◆ With automatic thermal closing mechanism



Extraction fans please see page 140!



Safe compartment, SF Type 30/1200, Dimensions W x D x H (mm) = 1080 x 518 x 422,5; Art. No. B80-2661-A

Model		SIS Type 30 / 600 GL	SIS Type 30 / 1200 GL
External dimensions W x D x H (mm)		595 x 595 x 1935	1195 x 595 x 1935
Internal dimensions W x D x H (mm)		480 x 519 x 1660	1080 x 519 x 1660
Glass door(s)		1 (hinged right)	2
Weight (kg)		190	298
Outer body: RAL 7035 - light grey	Material inner fittings		
Art. No., door(s): RAL 7035 - light grey	sheet steel	B80-2654-A	B80-2656-A
Art. No., door(s): RAL 1007 - daffodil yellow	sheet steel	B80-2655-A	B80-2657-A
Accessories	Material	Article No.	Article No.
Shelf	sheet steel	B80-2611-A	B80-2610-A
Safe compartment	B1	B80-2660-A	B80-2661-A