



LINGJACK ENGINEERING WORKS PTE LTD

No.1 Woodlands Terrace, Lingjack Industrial Building, Singapore 738471

Tel : (65) 67594163 Fax : (65) 67587513 Web site: www.combat.com.sg

Co Reg No. : 199103053M GST Reg no. : M2-0100375-0

Data Sheet No.: 20800800

1KG ABC Dry Powder Stored Pressure Fire Extinguisher



Extinguisher Model	C-1ASE
Extinguishing Medium	ABC Dry Chemical Powder
Propellant Type	Nitrogen
Capacity	1.0kg
Paint Primer/Finish	Zinc phosphate/ Epoxy polyester
Paint Colour	Signal Red (RAL3000)
Fire Class	A,B,C & Electrical
Fire Rating	5A/55B
Operating Temperature	-20 °C to +60 °C
Test Pressure	25kgf/cm ²
Max Working Pressure	14kgf/cm ²
Minimum Discharge Time	6.1 Sec
Minimum Discharge Range	3 meters
Safe Operating Distance	2 meters
Cylinder Material	Cold Rolled Steel Sheet
Operating Valve	Forged Brass
Height	313mm
Diameter	85mm
Full Weight	2.01kg
Empty Weight	1.01kg
Nominal Carton Size(LxMxH) (mm)	165x88x330
Approval	BS EN 3/ LPCB, TPED, MED, PSB, SETSCO

