



LINGJACK ENGINEERING WORKS PTE LTD

No.1 Woodlands Terrace, Lingjack Industrial Building, Singapore 738471

Tel : (65) 67594163 Fax : (65) 67587513 Web site: www.combat.com.sg

Co Reg No. : 199103053M GST Reg no. : M2-0100375-0

Data Sheet No.: 20801800

25Liter Foam Stored Pressure

Trolley Fire Extinguisher



Extinguisher Model	C-25FTP
Extinguishing Medium	SC-1 Foam
Propellant Type	Nitrogen- Stored Pressure
Capacity	25Ltr
Paint Primer/Finish	Zinc phosphate/ Epoxy polyester
Paint Colour	Signal Red (RAL3000)
Fire Class	A,B
Operating Temperature	+5°C to +60 °C
Test Pressure	25kgf/cm ²
Max Working Pressure	14kgf/cm ²
Minimum Discharge Time	60 Sec
Discharge Range	10 meters
Safe Operating Range	6 meters
Discharge Hose	6 meters with controllable discharge gun
Cylinder Material	Cold Rolled Steel Sheet
Operating Valve	CE Approved Brass Turn Valve
Height	925mm
Diameter	510mm
Full Weight	45kg
Empty Weight	20kg
Standards	BS EN 1866

