



LINGJACK ENGINEERING WORKS PTE LTD

No.1 Woodlands Terrace, Lingjack Industrial Building, Singapore 738471

Tel : (65) 67594163 Fax : (65) 67587513 Web site: www.combat.com.sg

Co Reg No. : 199103053M GST Reg no. : M2-0100375-0

Data Sheet No.: 20800100

2KG Halotron I Stored Pressure Fire Extinguisher



Extinguisher Model	C-2HSE
Extinguishing Medium	Halotron™ I
Propellant Type	Argon
Capacity	2.0kg
Paint Primer/Finish	Zinc phosphate/ Epoxy polyester
Paint Colour	Signal Red (RAL3000)
Fire Class	A,B,C & Electrical
Fire Rating	5A/34B
Operating Temperature	-20 °C to +60 °C
Test Pressure	25 bar
Max Working Pressure	6.9kgf/cm ²
Minimum Discharge Time	6.1 Sec
Minimum Discharge Range	3 meters
Safe Operating Distance	2 meters
Cylinder Material	Cold Rolled Steel Sheet
Operating Valve	Forged / Brass
Height (+/-3mm)	445mm
Diameter	98mm
Full Weight	3.76kgs
Empty Weight	1.76kgs
Nominal Carton	165x102x463
Size(LxMxH) (mm)	
Approval	EN3, PSB, SETSCO, TPED,

