



LINGJACK ENGINEERING WORKS PTE LTD

No.1 Woodlands Terrace, Lingjack Industrial Building, Singapore 738471

Tel : (65) 67594163 Fax : (65) 67587513 Web site: www.combat.com.sg

Co Reg No. : 199103053M GST Reg no. : M2-0100375-0

Data Sheet No.: 20806400

30kg Halotron I Stored Pressure Trolley Fire Extinguisher



Extinguisher Model	C-30HTP
Extinguishing Medium	Halotron™ I
Propellant Type	Stored Pressure
Capacity	30kg
Paint Primer/Finish	Zinc phosphate/ Epoxy polyester
Paint Colour	Signal Red (RAL3000)
Fire Class	A,B,C & Electrical
Operating Temperature	-20 °C to +60 °C
Test Pressure	25kgf/cm ²
Max Working Pressure	10kgf/cm ²
Discharge Time	17 Sec
Discharge Range	3.5 meters
Safe Operating Range	3 meters
Discharge Hose	6 meters with controllable discharge gun
Cylinder Material	Cold Rolled Steel Sheet
Operating Valve	CE Approved Brass Turn Valve
Height	920mm
Diameter	420mm
Full Weight	65kg
Empty Weight	35kg
Standards	BS EN 1866

