



LINGJACK ENGINEERING WORKS PTE LTD

No.1 Woodlands Terrace, Lingjack Industrial Building, Singapore 738471

Tel : (65) 67594163 Fax : (65) 67587513 Web site: www.combat.com.sg

Co Reg No. : 199103053M GST Reg no. : M2-0100375-0

Data Sheet No.: 20805400

50kg ABC Powder Stored Pressure Trolley Fire Extinguisher



Extinguisher Model	C-50ATP
Extinguishing Medium	ABC Dry Chemical Powder
Propellant Type	Nitrogen gas
Capacity	50kg
Paint Primer/Finish	Zinc phosphate/ Epoxy polyester
Paint Colour	Signal Red (RAL3000)
Fire Class	A,B,C & Electrical
Operating Temperature	-20 °C to +60 °C
Test Pressure	25kgf/cm ²
Max Working Pressure	14kgf/cm ²
Discharge Time	35 Sec
Discharge Range	10 meters
Safe Operating Range	6 meters
Discharge Hose	6 meters with controllable discharge gun
Cylinder Material	Cold Roll Steel Sheel
Operating Valve	CE Approved Brass Gas Bottle Valve
Height	980mm
Diameter	610mm
Full Weight	84kg
Empty Weight	34kg
Standards	BS EN 1866



