



LINGJACK ENGINEERING WORKS PTE LTD

No.1 Woodlands Terrace, Lingjack Industrial Building, Singapore 738471

Tel : (65) 67594163 Fax : (65) 67587513 Web site: www.combat.com.sg

Co Reg No. : 199103053M GST Reg no. : M2-0100375-0

Data Sheet No.: 20801700

9Liter Foam Stored Pressure Fire Extinguisher



Extinguisher Model	C-9FSE
Extinguishing Medium	AFFF Foam
Propellant Type	Nitrogen
Capacity	9.0Ltr
Paint Primer/Finish	Zinc phosphate/ Epoxy polyester
Paint Colour	Signal Red (RAL3000)
Fire Class	A,B
Fire Rating	34A/233B
Operating Temperature	+5°C to +60 °C
Test Pressure	25kgf/cm ²
Max Working Pressure	14kgf/cm ²
Minimum Discharge Time	60Sec
Minimum Discharge Range	4 meters
Safe Operating Distance	2 meters
Cylinder Material	Cold Rolled Steel Sheet
Operating Valve	Forged / Brass
Height	610mm
Diameter	181mm
Full Weight	13.36kg
Empty Weight	4.36kg
Nominal Carton Size(LxMxH) (mm)	197x197x625
Approval	BS EN 3/PSB, LPCB, TPED, MED, SETSCO

