



# LINGJACK ENGINEERING WORKS PTE LTD

No.1 Woodlands Terrace, Lingjack Industrial Building, Singapore 738471

Tel : (65) 67594163 Fax : (65) 67587513 Web site: [www.combat.com.sg](http://www.combat.com.sg)

Co Reg No. : 199103053M GST Reg no. : M2-0100375-0

Data Sheet No.: 20804500

## 9KG Purple K Dry Powder Stored Pressure Fire Extinguisher



Extinguisher Model	C-9PKSE
Extinguishing Medium	Purple K
Propellant Type	Nitrogen
Capacity	9.0kg
Paint Primer/Finish	Zinc phosphate/ Epoxy polyester
Paint Colour	Signal Red (RAL3000)
Fire Class	B,C & Electrical
Fire Rating	233B
Operating Temperature	-20 °C to +60 °C
Test Pressure	25kgf/cm <sup>2</sup>
Max Working Pressure	14kgf/cm <sup>2</sup>
Minimum Discharge Time	13.3Sec
Minimum Discharge Range	7 meters
Safe Operating Distance	2 meters
Cylinder Material	Cold Rolled Steel Sheet
Operating Valve	Forged / Brass
Height	610mm
Diameter	181mm
Full Weight	13.01kg
Empty Weight	4.01kg
Nominal Carton Size(LxMxH) (mm)	197x197x625
Approval	BS EN 3/PSB, LPCB, TPED

