## **EUROCHARGER II**

AUTOMATIC BATTERY CHARGER FOR TWO SEPARATE BATTERY SYSTEMS



FOR THE SPECIFIC NEEDS OF EMERGENCY VEHICLES

SUPPORTS PARASITIC LOADS

AUTO PRIORITISES THE FLATTER BATTERY

LOW FREQUENCY - LOW NOISE

RUGGED CONSTRUCTION FOR VEHICLE MOUNTING

INPUT VOLTAGE SELECTABLE, 115 OR 230 VOLTS

DESIGNED TO CE REQUIREMENTS

The Euro Charger II is a fully automatic battery charger designed to meet CE requirements.

Ruggedly constructed with two independently controlled outputs, it float charges the batteries and may be installed on the vehicle. Euro Charger II prioritises the flatter battery automatically. Extremely precise voltage control maintains the charger outputs constant with variations in load or line voltage inputs. Active current limiting limits the output current so as not to exceed its rated value when charging deeply discharged batteries or if the vehicle is started while charging.

Two unique remote displays are available as options for this charger. One provides a simple, 2 LED display. A green LED indicates that power is ON while a red LED indicates that output current is flowing from the charger. A second display, a dual bar graph, provides a graphic display of the charger output voltages.

MODEL #	091-117T-12	091-117-24
<b>VOLTAGE IN</b>	115V OR 230V AC 50/60HZ	
CURRENT IN	2.6A OR 1.3A	
<b>VOLTAGE OUT</b>	12	24
CURRENT OUT	15	6
INDICATOR	SEE BELOW	
WEIGHT	4.1KG	
OUTLINE	030	

## OPTIONAL REMOTE DISPLAYS



DUAL BAR GRAPH DISPLAY LED INDICATOR

LUDO McGURK SVE

UNIT 3 CROSSFIELD ROAD, HANDFORTH, CHESHIRE, SK9 3LN.

TEL: +44 1625 527 673 WEB: www.ludomcgurk.co.uk FAX: +44 1625 549 929 EMAIL: sales@ludomcgurk.co.uk

