# Mobile Rescue Sets

**JAWS OF LIFE** 



### Technical Data SC 350

Cutting force up to	85,430 lbs / 380 kN
Round steel up to dia. *	1.2 in. / 30 mm
Spreading force up to	25,400 lbs / 113 kN
Spreading distance	14.1 in. / 360 mm
Pulling force up to	10,228 lbs / 45.5 kN
Pulling distance	15 in. / 381 mm
Oil requirement	4 cu.in. / 66 cm <sup>3</sup>
Dimensions: Ixwxh	30.3 x 7.8 x 6.4 in.
	770 x 199 x 163 mm
Weight	32.2 lbs / 14.6 kg

\* According to EN 13204

## Technical Data P 620 OG

Gasoline engine	1.3 kW	
Output LP	122 cu.in/min / 2 l/min	
Output HP	39.7 cu.in/min / 0.65 l/min	
Capacity of oil reservoir	122 cu.in. / 2 l	
Usable oil capacity	97.6 cu.in. / 1.6 l	
Dimensions: lxwxh	14.2 x 12.4 x 15.4 in.	
	360 x 315 x 390 mm	
Weight:	33 lbs / 15 kg	
Dimensions of storage case: lxwxh	36 x 15.2 x 20.3 in.	
	915 x 385 x 515 mm	
Weight of storage case:	161.8 lbs / 73.4 kg	
© Copyright 07/2008 LUKAS Hydraulik GmbH · Subject to revision		

High Performance Rescue Sets for fast intervention and mobile operations stored in compact transport cases.

# **RS 2**

- Combi Tool SC 350
- Chain Set KSV 8
- Telescopic Ram R 420

REAMILINE

TECHNOLOGY

- Super Compact Power Unit P 620 OG with couplings
- 16 ft. / 5 m Extension Hose pair

#### Technical Data R 420

Total stroke	22.6 in. / 575 mm
Stroke / lifting cap. piston 1	11.6 in. / 60,000 lbs
	295 mm / 267 kN
Stroke / lifting cap. piston 2	11 in. / 29,900 lbs
	280 mm / 133 kN
Total extended length	41.4 in. / 1055 mm
Oil requirement	86 cu.in. / 1410 cm <sup>3</sup>
Dimensions retracted: Ixwxh	18.8 x 4.4 x 8.3 in
	480 x 112 x 211 mm
Weight	37.3 lbs / 16.9 kg

