





Engineered  
Quality



## multi-purpose pump NP 8 D

Wastewater · with Diesel engine  
Diesel engine



### RANGE OF USE

Self-priming centrifugal pump applicable for wastewater, light fuel oil, Diesel fuel, and other non-aggressive liquids.

temperature of medium to be pumped max: 100 °C

density of medium max: 1.1 kg/dm<sup>3</sup>

pH value min: 5

pH value max: 8

### TECHNICAL SPECIFICATIONS

Engine: 4-stroke Diesel engine HATZ 1B20

engine power P1: 3.4 kW

weight: 58 kg

Height H (max.): 28 m

Rate Q (max.): 850 l/min

companion dimensions: G 2.5"

STORZ - coupler: B

Solids passage: 10 mm

Delivery rate Q l/min	850	800	680	360	0
Delivery height H m (WC)	0	5	10	20	28

### SPECIFICS

- Self-priming from 8,4
- Wheeled unit on request
- E-Start with Starter / Generator and 12 V-battery on request
- maintenance-free
- dry-running safe

#### Features engine:

- Direct fuel injection
- Automatic decompression
- Dry air filter with integrated pre-cleaner
- Lubrication by pressurised circulation of oil

### MATERIALS

**pump body:** Aluminium alloy acc. to DIN EN 1706\*

**blade wheel:** Special cast iron acc. to DIN EN 1561

**control device:** Special cast iron acc. to DIN EN 1561

**seals:** Mineraloil resistant rubber

: Face seal carbon / carbid