

- Filters out CO and smoke
- Universal size
- Easily fitted with quick donning

- Minimal training required
- **●** EN 403:2004 approved

Most victims of fire are not injured by heat or flames but rather by smoke and gases, especially carbon monoxide. The S-CAP Fire Escape Hood is simple to don and use and is effective within seconds, using a filter designed for a minimum rated service time of 15 minutes.

## Features and Benefits S-CAP Fire Escape Hood

- Highly visible yellow hood
- Adjustable head harness on the outside of the hood, with cotton neck seal for easy donning
- · Wide field of view lens
- Heat-resistant against brief flame contact and elevated temperatures





Escape hood designed for protection from smoke and gases generated by fires.

- Fits a wide variety of head and face sizes and is directly connected to a

## **Multi-Purpose Filter**

- P2 Filter -filters 94% at 95 lpm (similar to N95) and is oil-resistant
- Protects against smoke, carbon monoxide, acrolein, hydrogen chloride, hydrogen cyanide, and sulfur dioxide

## Storage

- Hood is protected and stored in a vacuum-sealed aluminized foil bag
- Donning procedure is illustrated on the foil bag
- Cardboard Box storage option contains one foil bag and donning instructions
- · Wall Box storage option contains one hood in a foil bag and donning instructions

## **Specifications**

Hood: coated PVC Material:

Neck seal: cotton Lens: **PET** 

Inner mask: natural rubber, gray

> Filter: Multi-purpose filter [CO, gases from fire and particles P2]

Weight: 1.2 lb. (ready to use) Size: Adult universal Service time: minimum 15 minutes

**Breathing resistance:** Inhalation resistance approx. 1.2 mbar

Exhalation resistance approx. 0.5 mbar

**Storage Options** 

Cardboard Box: 11 x 6 x 4.5" (H x W x D)

> Wall Box: 11 x 6 x 5"

Storage life: Maintenance-free for 4 years. Up to 10 years with testing

**Approvals:** EN 403:2004

**Ordering Information** 

10064644 S-CAP Fire Escape Hood in cardboard box 10064645 S-CAP Fire Escape Hood in wall-mount box

Note: This Bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.

Corporate Headquarters P.O. Box 426, Pittsburgh, PA 15230 USA Phone 412-967-3000 www.MSAnet.com

**U.S. Customer Service Center** 1-800-MSA-2222 Phone 1-800-967-0398 Fax

MSA Canada

416-620-4225 Phone 416-620-9697

MSA Mexico

Phone 52-55 21 22 5770 Fax 52-55 5359 4330

MSA International

412-967-3354 412-967-3451

Offices and representatives worldwide

