

GTP - Air/hydraulic telescopic jacks

Reliability. All NIKE trolley jacks feature modern design and are designed to incorporate large safety margins. A safety valve on all models protects against overloading.

Service. Easily replaceable components make NIKE trolley jacks simple to service. We have a large network of dealers and service agents around the world.

GTP - models

- Easy to manoeuvre.
- Telescopic ram provides high maximum height.
- Long handle for good accessibility.

Capacity - 1. stage: 60 ton, 2. stage: 30 ton, 3. stage: 18 ton

Please observe that GTP60 requires between 8 bar and 12 bar air pressure.





Technical data

Name	Capacity ton	Min. height mm	Max. height mm	Extension mm	Hydr. stroke mm	Req. air pressure MPa (bar)	Weight kg
GTP60	60	180	617	200	237	0.8 (8)	70



www.nikehydraulics.com

NIKE HYDRAULICS AB

Box 1107
631 80 Eskilstuna
SWEDEN
Tel +46 16 - 16 82 00
Fax +46 16 - 13 93 16
info@nikehydraulics.se

NIKE HYDRAULICS Inc.

3980 W. Albany, Unit #1
MCHENRY, IL 60050
USA
Tel + 1 815 385 7777
Fax + 1 815 385 7776
info@nikehydraulics.com

NIKE POWER EQUIPMENT Ltd.

Unit 6, Stechford Trading Estate
Lyndon Road, Stechford
BIRMINGHAM B33 8BU, UK
Tel +44 121 789 77 07
Fax +44 121 789 68 66
info@nikehydraulics.co.uk