

Manufacturer:

OGNIOCHRON S.A.

ul. Przemysłowa 42, 34-120 Andrychów, Poland  
tel.: +48 33 875 10 70 ext. 161, e-mail: export@ogniochron.eu

www.ogniochron.eu

# ogniochron

## Application

Applicable in paint shops, power industry, industrial halls and everywhere where usage of extinguishing powders is not recommended due to presence of devices sensitive to dust and impurities. The extinguisher does not leave any remains after application.



## Basic features

- Easy and ergonomic operation.
- New generation of light, steel cylinder.
- Economical maintenance and service.
- Valve equipped with bursting disc.
- Construction of the valve enables temporary interruption of extinguishing.
- Cylinder of extinguisher covered with polyester paint, resistant to UV radiation.


## Quality and safety

Manufactured according to requirements of domestic and EU markets on the basis of certified quality system ISO 9001. Fulfills requirements of European Standard EN3 and Safety Directive PED 2014/68/UE.



## Technical data

Extinguishing efficiency	34B
Weight of extinguishing agent	2 kg
Operation time	min. 6 s
Cylinder test pressure	315 bar
Operating temperature	-20 °C/+60 °C
Total weight	~7 kg
Fire under voltage	1000 V
Total height (A)	543 mm
Cylinder diameter (B)	105 mm



## Carbon dioxide extinguisher

### GS-2x B

