### Manufacturer:

### **OGNIOCHRON S.A.**

ul. Przemysłowa 42, 34-120 Andrychów, Poland tel.: +48 33 875 10 70 ext. 161, e-mail: export@ogniochron.eu

www.ogniochron.eu



# **Application**

Designed to protect devices with lithium-ion batteries like: cordless power tools, scooters and electric skateboards, etc. An innovative extinguishing agent quickly cools the battery and extinguishes the flames.





## **Basic features**

- Easy and ergonomic in operation.
- Fast and effective in extinguishing.
- Economical maintenance and service.
- Cut-off valve behind the pressure indicator makes control of fire extinguisher easier.
- Construction of the valve enables temporary interruption of extinguishing.
- Cylinder of fire extinguisher covered with polyester paint, resistant to UV radiation.
- Interior of cylinder protected with anticorrosive layer.

## **Quality and safety**

Manufactured according to requirements of domestic and EU markets on the basis of certified quality system ISO 9001. Fulfills requirements of Safety Directive PED 2014/68/UE.





### **Technical data**

Amount of extinguishing agent	61
Working agent	$N_2$
Operating time	15 s
Cylinder test pressure	27 bar
Operation pressure	15 bar
Temperature range	+5 °C/+60 °C
Total weight	~9,3 kg
Fire under voltage	1000 V
Total height (A)	502 mm
Cylinder diameter (B)	160 mm



Extinguishing device for lithium battery

**VER-DIS 6x** 

**VER+DIS** 

