

SNAKE

Flow: 150 GPM @ 100 PSI - 2000 l/mn @ 7 bars
 Horizontal Range: Full 360°
 Vertical Range: +75° to -75°
 Extremely Compact 16" X 14"
 Vertical Travel Control Locking Handle
 Grease Fitting
 Waterway 1.5"
 Red Epoxy Finish
 Made Primarily of Aluminum
 Flange, 1.5" or 2.5" inlet
 1.5" outlet

Code	Description	Weight
10973	SNAKE monitor specify inlet and 1.5" M outlet	82 lb



PRIMATOR 3000

Flow: 1000 GPM @ 100 PSI - 3700 l/mn @ 7 bars
 Horizontal Range: Full 360°
 Vertical Range: +90° to -70°
 Extremely Compact 26" X 29"
 Vertical Travel Control Locking Handle
 Grease Fitting
 Waterway 3.0" with Anti -Turbulence Ribbing
 Red Epoxy Finish
 Made Primarily of Anodized Aluminum Heat-Treated against Corrosion,
 Marine Environment and Foam
 Flange or 2.5" inlet 2.5" outlet

Code	Description	Weight
1507	PRIMATOR monitor flange inlet and 2.5" M outlet	19 lb



AZIMUTOR 3000

Flow: 1000 GPM @ 100 PSI - 3700 l/mn @ 7 bars
 Horizontal Range: Full 360°
 Vertical Range: +90° to -15°
 Extremely Compact 28" X 14"
 Vertical Travel Control Wheel Handle with Safety Pull Pin
 Grease Fitting
 Waterway 3.0" with Anti -Turbulence Ribbing
 Red Epoxy Finish
 Made Primarily of Anodized Aluminum Heat-Treated against Corrosion,
 Marine Environment and Foam
 Flange or 2.5" inlet 2.5" outlet

Code	Description	Weight
13605	AZIMUTOR monitor flange inlet and 2.5" M outlet	44 lb

