

SPECIFICATIONS

HALOTRON 1

Red glossy polyester coated steel cylinder with bracket. The stored pressure environment friendly HCFC-123 “Clean Agent” is non-conductive, non-corrosive and rapidly evaporates leaving no residue. Recommended for electrical equipment fires.

CARBON DIOXIDE (Co2)

Red glossy polyester coated aluminum cylinder with discharge horn and wall bracket. Pressurized content is a non-contaminating odorless gas. Model 3405NM non-magnetic with white paint finish for use in MRI facilities.



MODEL 3101 (Shown)

PRODUCT OPTIONS

SEE 3900 SERIES CATALOG SECTION FOR OPTIONAL FIRE EXTINGUISHER MOUNTING BRACKETS

MODEL SELECTION

- 3101** ABC 1.4# Halotron 1
- 3102** ABC 2.5# Halotron 1
- 3105** ABC 5# Halotron 1
- 3111** ABC 11# Halotron 1
- 3115** ABC 15.5# Halotron 1
- 3405** 5# Carbon Dioxide
- 3405NM** 5# Carbon Dioxide Non-Magnetic
- 3410** 10# Carbon Dioxide
- 3415** 15# Carbon Dioxide
- 3420** 20# Carbon Dioxide

<p>Call Potter Roemer for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer assumes no responsibility for use of void or superceded data. © Copyright Potter Roemer, Member of Morris Group International™ Please visit potterroemer.com for most current specifications.</p> <p>3100/3400 SERIES Date: 4/12/23</p>	<p>MEMBERSHIP</p>		<p>POTTER ROEMER</p> <p>Headquarters: P.O. Box 3527 City of Industry, CA 91744 U.S.A. Los Angeles Area 800-366-3473 626-855-4890</p> <p>Also in: New York (800) 526-4592 Chicago (800) 547-3473 Atlanta (800) 762-0542 Miami (833) 744-3473 Dallas (866) 644-3473</p> <p>www.potterroemer.com</p>
--	--------------------------	--	--

MODEL DIMENSIONS

HALOTRON 1							
Model No.	Size lbs./kg	U/L Rating	Overall Height in./cm	Dia. In. / cm	Overall Width in./cm	Range of Stream ft./m	Type Discharge
3101	1.4 / .63	1B:C	10" / 25.4	2-5/8" / 6.6	3-1/2" / 8.9	6'-8" / 1.8-2.4	Nozzle
3102	2.5 / 1.1	2B:C	15-1/2" / 39.4	3" / 7.6	6-3/8" / 16.1	6'-10" / 1.8-3	Nozzle
3105	5 / 2.2	5B:C	15-1/4" / 38.7	4-1/4" / 10.8	5-3/4" / 14.6	9'-15' / 2.7-4.6	Nozzle
3111	11 / 5	1A:10B:C	21-7/8" / 55.5	6" / 15.2	9-1/4" / 23.5	9'-15' / 2.7-4.6	Hose & Nozzle
3115	15.5 / 7	2A:10B:C	21-7/8" / 55.5	6" / 15.2	9-1/4" / 23.5	12'-18' / .36-5.4	Hose & Nozzle



CARBON DIOXIDE (CO ₂)							
Model No.	Size lbs./kg	U/L Rating	Overall Height in./cm	Dia. In./cm	Overall Width in./cm	Range of Stream ft./m	Type Discharge
3405	5 / 2.3	5B:C	17-3/4" / 45	5-1/4" / 13.3	8-1/4" / 20.9	3'-8" / .91-2.4	Horn
3405NM*	5 / 2.3	5B:C	17-3/4" / 45	5-1/4" / 13.3	8-1/4" / 20.9	3'-8" / .91-2.4	Horn
3410	10 / 4.5	10B:C	24" / 61	7" / 17.8	12" / 30.4	3'-8" / .91-2.4	Hose & Horn
3415	15 / 6.8	10B:C	30" / 76.2	7" / 17.8	12" / 30.4	3'-8" / .91-2.4	Hose & Horn
3420	20 / 9	10B:C	30" / 76.2	8" / 20.3	13" / 33	3'-8" / .91-2.4	Hose & Horn



* Non-Magnetic approved for use in MRI facilities.

<p>Call Potter Roemer for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer assumes no responsibility for use of void or superseded data. © Copyright Potter Roemer, Member of Morris Group International™ Please visit potterroemer.com for most current specifications.</p> <p>3100/3400 SERIES</p>	<p>MEMBERSHIP</p> 	<p>POTTER ROEMER</p> <p>Headquarters: P.O. Box 3527 City of Industry, CA 91744 U.S.A. Los Angeles Area 800-366-3473 626-855-4890</p> <p>Also in: New York (800) 526-4592 Chicago (800) 547-3473 Atlanta (800) 762-0542 Miami (833) 744-3473 Dallas (866) 644-3473</p> <p>www.potterroemer.com</p>
--	---	--