

SPECIFICATIONS

DRY CHEMICAL TYPE

Red glossy polyester coated steel cylinder, carriage and hose hanger assembly. Quick release, non-kink hose with positive grip nozzle. Semi-pneumatic tires. Size, agent, and method of operation as selected by figure number.

HALOTRON TYPE

Red glossy polyester coated steel DOT cylinder, carriage, and hose rack. Quick opening chrome plated brass valve. FAA approved as clean agent for both ramp use and on-board aircraft.

CARBON DIOXIDE TYPE

Red glossy polyester coated steel cylinder, black carriage. Quick release, non-kink hose with shock resistant, rubber insulated horn and handle. Diffusion tip and safety release disc in discharge valve. Pressurized content is a non-contaminating, non-conductive odorless gas. Semi-pneumatic tires. Sizes as selected by figure number.

WHEEL MODEL SELECTION

- 3500 SERIES** Dry Chemical
- 3560 SERIES** Halotron 1
- 3600 SERIES** Carbon Dioxide

EXTINGUISHER MODEL SELECTION

- 3510** ABC Stored Pressure Multi-Purpose Dry Chemical
- 3520** ABC Nitrogen Cylinder Operated Multi-Purpose Dry Chemical
- 3525** ABC Stored Pressure Multi-Purpose Dry Chemical
- 3530** BC Stored Pressure Purple-K Dry Chemical
- 3540** BC Nitrogen Cylinder Operated Purple-K Dry Chemical
- 3545** BC Stored Pressure Dry Chemical
- 3550** BC Nitrogen Cylinder Operated Dry Chemical
- 3560** 65 lb. Stored Pressure Halotron 1
- 3565** 150 lb. Stored Pressure Halotron 1
- 3610** BC Self Expellent Carbon Dioxide
- 3620** BC Self Expellent Carbon Dioxide



PRODUCT OPTIONS

NO AVAILABLE OPTIONS

Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer - Fire Pro assumes no responsibility for use of void or superseded data. © Copyright Potter Roemer - Fire Pro, Member of Morris Group International™ Please visit potterroemer.com for most current specifications.

3500/3600 SERIES Date: 12/27/21

MEMBERSHIP



FIRE EQUIPMENT
MANUFACTURERS'
ASSOCIATION

ONFSA
NATIONAL FIRE SPRINKLER ASSOCIATION, INC.



CASPE
American Society of
Plumbing Engineers














POTTER ROEMER/FIRE PRO

Headquarters:
P.O. Box 3527
City of Industry, CA
91744 U.S.A.
Los Angeles Area
800-366-3473
626-855-4890

Also in:
New York (800) 526-4592
Chicago (800) 547-3473
Atlanta (800) 762-0542
Miami (833) 744-3473
Dallas (866) 644-3473

www.potterroemer.com

MODEL DIMENSIONS

Model No.	Type	Agent	Function	Size (lbs.)	Method of Operation	UL/Rating	H E I G H T	W I D T H	D E P T H	Hose Length
3510	ABC Multi-purpose Dry Chemical	Ammonium Phosphate		50 lb.	SP	20A:160B:C	46"	21-1/2"	24"	25'
3520	ABC Multi-purpose Dry Chemical	Ammonium Phosphate		125 lb.	NC	30A:240B:C	45"	24"	36"	50'
3525	ABC Multi-purpose Dry Chemical	Ammonium Phosphate		125 lb.	SP	30A:240B:C	53-1/2"	28"	40"	50'
3530	Purple-K Dry Chemical	Potassium Bicarbonate		50 lb.	SP	160B:C	46"	21-1/2"	24"	25'
3540	Purple-K Dry Chemical	Potassium Bicarbonate		125 lb.	NC	320B:C	45"	24"	36"	50'
3545	Dry Chemical	Sodium Bicarbonate		50 lb.	SP	160B:C	46"	21-1/2"	24"	25'
3550	Dry Chemical	Sodium Bicarbonate		150 lb.	NC	240B:C	45"	24"	36"	50'
3560	Halotron 1	Halotron		65 lb.	SP	4A:80BC	58"	28"	39"	50'
3565	Halotron 1	Halotron		150 lb.	SP	10A:120BC	64"	37"	43"	50'
3610	Carbon Dioxide	Carbon Dioxide		50 lb.	SE	20B:C	47"	23"	48"	40'
3620	Carbon Dioxide	Carbon Dioxide		100 lb.	SE	20B:C	47"	23"	48"	40'

NOTE: 3620 provided with two cylinders.

METHOD OF OPERATION: SP = Stored Pressure

NC = 23 Cubic Foot Nitrogen Cylinder with Handwheel valve

SE = Self Expellent



3500 SERIES



3600 SERIES

Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer - Fire Pro assumes no responsibility for use of void or superseded data. © Copyright Potter Roemer - Fire Pro, Member of Morris Group International™ Please visit potterroemer.com for most current specifications.

3500/3600 SERIES

MEMBERSHIP



FIRE EQUIPMENT
MANUFACTURERS'
ASSOCIATION



POTTER ROEMER/FIRE PRO

Headquarters:
P.O. Box 3527
City of Industry, CA
91744 U.S.A.
Los Angeles Area
800-366-3473
626-855-4890

Also in:
New York (800) 526-4592
Chicago (800) 547-3473
Atlanta (800) 762-0542
Miami (833) 744-3473
Dallas (866) 644-3473

www.potterroemer.com