

SPECIFICATIONS

Potter Roemer/ Fire Pro® electrically operated monitor nozzles for use in remote control applications. Nozzles easily change from solid bore to fog with the flick of the switch without shutting down. Standard 24V motor (or 12V on request) is totally enclosed and sealed and features manual override when electrical power fails.



FP10818E (Shown)

REGULARLY FURNISHED

- Combination fog and solid bore
- Hardcoat anodized aluminum
- Spinning teeth

MODEL	INLET In (mm)	WEIGHT Lbs (kg)	GPM (lpm)
FP10818E	1-1/2" (38)	7 (3.2)	15, 30, 45 (56, 115, 170)
FP10819E	1-1/2" (38)	7 (3.2)	60, 95, 125 (946, 1325, 1893)
FP10820E	1-1/2" (38)	7 (3.2)	200, 250, 350 (757, 949, 1325)

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

<p>Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacture's tolerance and may change without notice. Potter Roemer - Fire Pro assumes no responsibility for use of void or superceded data. Please visit potterroemer.com for most current specifications</p> <p>EC-FP10818 Revised: 09/05/18</p>	<p>MEMBERSHIP</p> 	<p>POTTER ROEMER/FIRE PRO</p> <p>Headquarters: P.O. Box 3527 City of Industry, CA 91744 U.S.A. Los Angeles Area 800-366-3473 626-855-4890</p> <p>Also in: New York (800) 526-4592 Chicago (800) 547-3473 Atlanta (800) 762-0542 Miami (866) 961-3473 Dallas (866) 644-3473</p> <p>www.potterroemer.com</p>
--	---	---