

SPECIFICATIONS

Potter Roemer/ Fire Pro® Master Stream selectable gallonage monitor nozzles are combination pattern, master stream nozzles with four distinct, calibrated and selectable flow settings. Precision machining ensures ease of operation when changing patterns at all pressure ranges.



FP10848-BC (Shown)

REGULARLY FURNISHED

- Combination fog and straight stream
- Lightweight alloy or brass construction
- Spinning teeth
- Low maintenance components
- Heavy duty protective bumper

MODEL	INLET In (mm)	LENGTH In (mm)	WEIGHT Lbs (kg)	GPM (lpm)
FP10848	2-1/2" (64)	9-1/3" (236)	8-1/2 (3.9)	500, 750, 1000, 1250 (1893, 2839, 3785, 4732)
FP10848-BC	2-1/2" (64)	9-1/3" (236)	22 (10)	500, 750, 1000, 1250 (1893, 2839, 3785, 4732)
FP10849	2-1/2" (64)	9-1/3" (236)	8-1/2 (3.9)	350, 500, 750, 1000 (1325, 1893, 2839, 3785)
FP10849-BC	2-1/2" (64)	9-1/3" (236)	22 (10)	350, 500, 750, 1000 (1325, 1893, 2839, 3785)

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

<p>Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacture's tolerance and may change without notice. Potter Roemer - Fire Pro assumes no responsibility for use of void or superceded data. Please visit potterroemer.com for most current specifications</p> <p>MS-FP10848 Revised: 09/05/18</p>	<p>MEMBERSHIP</p> 	<p>POTTER ROEMER/FIRE PRO</p> <p>Headquarters: P.O. Box 3527 City of Industry, CA 91744 U.S.A. Los Angeles Area 800-366-3473 626-855-4890</p> <p>Also in: New York (800) 526-4592 Chicago (800) 547-3473 Atlanta (800) 762-0542 Miami (866) 961-3473 Dallas (866) 644-3473</p> <p>www.potterroemer.com</p>
--	---	---