

SPECIFICATIONS

Potter Roemer/ Fire Pro® Master Stream self-inducting monitor nozzles are designed for inducting foam at pre-set flow rates.



FP10881-BC (Shown)

REGULARLY FURNISHED

- Brass construction
- Quick connect foam inlet

MODEL	INLET In (mm)	PROPORTION CAPABILITY	LENGTH In (mm)	WEIGHT Lbs (kg)	GPM (lpm)
FP10881-BC	1-1/2" (38)	3%, 6%	6-3/8" (160)	10 (4.5)	150 (550)
FP10883-BC	1-1/2" (38)	3%	6-3/8" (160)	10 (4.5)	225 (850)

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacture's tolerance and may change without notice. Potter Roemer - Fire Pro assumes no responsibility for use of void or superceded data. Please visit potterroemer.com for most current specifications

MS-FP10881

Revised: 08/24/20

MEMBERSHIP



FIRE EQUIPMENT
MANUFACTURERS'
ASSOCIATION

ONFSA
NATIONAL OPEN SPRINKLER ASSOCIATION, INC.



CASPE
American Society of
Plumbing Engineers



POTTER ROEMER/FIRE PRO

Headquarters:
P.O. Box 3527
City of Industry, CA
91744 U.S.A.
Los Angeles Area
800-366-3473
626-855-4890

Also in:
New York (800) 526-4592
Chicago (800) 547-3473
Atlanta (800) 762-0542
Miami (866) 961-3473
Dallas (866) 644-3473

www.potterroemer.com