

SPECIFICATIONS

Potter Roemer/ Fire Pro® Master Stream self-inducting monitor nozzles are designed for inducting foam at pre-set flow rates.



FP-10889-BC (Shown)

REGULARLY FURNISHED

- Brass construction
- 9' 1-1/2" industrial grade hose and 15" tube
- Quick connect foam inlet

MODEL	INLET In (mm)	PROPORTION CAPABILITY	LENGTH In (mm)	WEIGHT Lbs (kg)	GPM (lpm)
FP10889-BC	2-1/2" (65)	1%, 3%	9-1/2" (241)	18-3/4 (8.5)	1000 (3800)

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

<p>Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacture's tolerance and may change without notice. Potter Roemer - Fire Pro assumes no responsibility for use of void or superceded data. Please visit potterroemer.com for most current specifications</p> <p>MS-FP10889 Revised: 09/05/18</p>	<p>MEMBERSHIP</p> 	<p>POTTER ROEMER/FIRE PRO</p> <p>Headquarters: P.O. Box 3527 City of Industry, CA 91744 U.S.A. Los Angeles Area 800-366-3473 626-855-4890</p> <p>Also in: New York (800) 526-4592 Chicago (800) 547-3473 Atlanta (800) 762-0542 Miami (866) 961-3473 Dallas (866) 644-3473</p> <p>www.potterroemer.com</p>
--	---	---