



Fire Hydrant by Others

**Hydrant Mount** 2-1/2" (64mm) or 3" (76mm) 150# ASA raised face flange discharge with 2-1/2" (64mm) NH female swivel inlet. "C" clamp hydrant bracket support arms are designed to fit on virtually any hydrant style. Flange outlet ideal to mount flange base monitor on butterfly valve. Red polyester powder coat.

**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

<p>Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacture's tolerance and may change without notice. Potter Roemer - Fire Pro assumes no responsibility for use of void or superceded data. Please visit <a href="http://potterroemer.com">potterroemer.com</a> for most current specifications</p> <p><b>FP3530</b></p> <p>Revised: 09/07/18</p>	<p><b>MEMBERSHIP</b></p>       	<p><b>POTTER ROEMER/FIRE PRO</b></p> <p>Headquarters: P.O. Box 3527 City of Industry, CA 91744 U.S.A. Los Angeles Area 800-366-3473 626-855-4890</p> <p>Also in: New York (800) 526-4592 Chicago (800) 547-3473 Atlanta (800) 762-0542 Miami (866) 961-3473 Dallas (866) 644-3473</p> <p><a href="http://www.potterroemer.com">www.potterroemer.com</a></p>
--	--	---