

SPECIFICATIONS


Potter Roemer/ Fire Pro® Master Stream self-inducting monitor nozzles are designed for inducting foam at pre-set flow rates.



FP500-HF (Shown)

REGULARLY FURNISHED

- Brass construction
- Interchangeable orifice plates
- Proportioning capability of 1/2, 1, 3 and 6%
- 9' 1-1/2" industrial grade hose and 15" tube
- Quick connect foam inlet



Foam Orifice Plates

MODEL	INLET In (mm)	PROPORTION CAPABILITY	LENGTH In (mm)	WEIGHT Lbs (kg)	GPM (lpm)
FP350B-HF	2-1/2" (65)	1/2%-6%	5-3/4" (145)	21-1/2 (10)	350 (1325)
FP500B-HF	2-1/2" (65)	1/2%-6%	5-3/4" (145)	21-1/2 (10)	500 (1900)
FP750B-HF	2-1/2" (65)	1/2%-6%	5-3/4" (145)	21-1/2 (10)	750 (2839)

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacture's tolerance and may change without notice. Potter Roemer - Fire Pro assumes no responsibility for use of void or superceded data. Please visit potterroemer.com for most current specifications

MS-FP500-HF

Revised: 09/05/18

MEMBERSHIP



FIRE EQUIPMENT
MANUFACTURERS'
ASSOCIATION

ONFSA
NATIONAL IRRE SPRINKLER ASSOCIATION, INC.



CASPE
American Society of
Plumbing Engineers



POTTER ROEMER/FIRE PRO

Headquarters:
P.O. Box 3527
City of Industry, CA
91744 U.S.A.
Los Angeles Area
800-366-3473
626-855-4890

Also in:
New York (800) 526-4592
Chicago (800) 547-3473
Atlanta (800) 762-0542
Miami (866) 961-3473
Dallas (866) 644-3473

www.potterroemer.com