



SPECIFICATION SHEET

16-939



G-TEK® POLYKOR® X7™ SEAMLESS KNIT POLYKOR® X7™ BLENDED GLOVE WITH DOUBLE DIP FULL NITRILE COATING AND MICROSURFACE GRIP

- Seamless construction offers increased comfort and breathability
- PolyKor® blended shell with X7™ technology offers high cut resistance and durability with ultra-thin liners
- Double dipped with full smooth nitrile coating for maintaining dry hands in oily environments
- Nitrile Microsurface coated palm and fingertips provide a superior grip in dry, wet, and oily conditions by reacting like tiny suction cups that attach themselves firmly to the material being handled
- Touchscreen compatible to allow the user to operate a touch screen phone or device without removing gloves
- Knit Wrist helps prevent dirt and debris from entering the glove
- Color coded hems for easy size identification
- Microsurface nitrile palm provides excellent grip in dry, wet and oily conditions

APPLICATIONS

- Finishing & inspection
- Electronics
- General duty
- Small parts assembly
- Construction
- Maintenance

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C).

TECHNICAL DATA

MATERIAL	PolyKor® w/ X7™ Technology / Nitrile Double Dip Coating				
CONSTRUCTION	18 Gauge seamless knit				
COLOR	Shell: ■ Blue / Coating: ■ Black				
SIZES	S - XXL				
PACKAGING	1 pair per bag, 12 pairs per dozen, 6 dozen per case				
CASE DIMENSIONS	17.3" x 11.8" x 11.0" / 44cm x 30cm x 28cm				
CASE WEIGHT	S	M	L	XL	XXL
	7.5 lbs 3.4 kgs	8.4 lbs 3.8 kgs	10.1 lbs 4.6 kgs	10.4 lbs 4.7 kgs	10.6 lbs 4.8 kgs
COO	China				



BARCODES


ITEM	BAG	DOZEN	CASE
■ 16-939/S	616314266058	01616314266057	02616314266056
■ 16-939/M	616314266065	01616314266064	02616314266063
■ 16-939/L	616314266072	01616314266071	02616314266070
■ 16-939/XL	616314266089	01616314266088	02616314266087
■ 16-939/XXL	616314266096	01616314266095	02616314266094

DIMENSIONS (in/cm)

	S	M	L	XL	XXL
A	9.4 / 24	10 / 25.5	10.4 / 26.5	10.8 / 27.5	11.2 / 28.5
B	3.9 / 10	4.1 / 10.5	4.3 / 11	4.5 / 11.5	4.7 / 12
H	■ Red	■ Yellow	■ Brown	■ Black	■ Blue

PERFORMANCE PROPERTIES

EN388: 4X42D	ASTM F2992-15 ANSI Cut Level A4 (Adopted by ANSI/ISEA 02/16)					
ABRASION	0	1	2	3	4	-
CUT	X	1	2	3	4	5
TEAR	0	1	2	3	4	-
PUNCTURE	0	1	2	3	4	-
CUT (TDM-100)	A	B	C	D	E	F



PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: (800) 262-5755 • (518) 861-0133 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobal.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.