



# SPECIFICATION SHEET

## 16-MPH430



### G-TEK® POLYKOR® SEAMLESS KNIT BLENDED GLOVE WITH NITRILE MICROSURFACE COATED PALM & FINGERTIPS - TPR IMPACT PROTECTION

- Seamless construction offers increased comfort and breathability
- PolyKor® blended shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Nitrile Microsurface coated palm and fingertips provide a superior grip in dry, wet and oily conditions by reacting like tiny suction cups that attach themselves firmly to the material being handled
- Double-dipped palm and fingertips provide added abrasion resistance
- Knit Wrist helps prevent dirt and debris from entering the glove
- Color coded hems for easy size identification
- Heavyweight Thermo Plastic Rubber (TPR) provides back-of-hand impact resistance to knuckles and fingers by dispersing impact force energy away from the bone, without sacrificing dexterity

### APPLICATIONS

- Construction
- Manufacturing
- Assembly
- Shipping/Transportation
- Automotive

### CARE INSTRUCTIONS

Not recommend for washing. Soak gloves in 30-40°C water, and hang in a cool location to dry.



### TECHNICAL DATA

MATERIAL	PolyKor® Shell / Nitrile Coating / Impact TPR			
CONSTRUCTION	13 Gauge seamless knit			
COLOR	Shell: ■ Salt and Pepper; Coating: ■ Black; TPR: ■ Gray/Red			
SIZES	M - XXL			
PACKAGING	1 pair per bag, 6 pairs per inner pack, 3 dozen per case			
CASE DIMENSIONS	20.5" x 11.8" x 9" / 52cm x 30cm x 23cm			
CASE WEIGHT	M	L	XL	XXL
	17.2 lbs 7.8 kgs	17.9 lbs 8.1 kgs	18.5 lbs 8.4 kgs	19.8 lbs 9.0 kgs
COO	China			

### BARCODES

ITEM	BAG	PAIR	CASE
■ 16-MPH430/M	616314267017	01616314267016	02616314267015
■ 16-MPH430/L	616314267024	01616314267023	02616314267022
■ 16-MPH430/XL	616314267031	01616314267030	02616314267039
■ 16-MPH430/XXL	616314267048	01616314267047	02616314267046


### DIMENSIONS (in/cm)

	M	L	XL	XXL
<b>A</b>	10 / 25.5	10.4 / 26.5	10.8 / 27.5	11.2 / 28.5
<b>B</b>	4.5 / 11.5	4.6 / 11.7	4.7 / 11.9	4.8 / 12.3
<b>H</b>	■ Yellow	■ Brown	■ Black	■ Blue

### PERFORMANCE PROPERTIES

EN388: 4X41DP ASTM F2992-15 ANSI Cut Level A4 (Adopted by ANSI/ISEA 02/16)

ABRASION	0	1	2	3	4	-
CUT	X	1	2	3	4	5
TEAR	0	1	2	3	4	-
PUNCTURE	0	1	2	3	4	-
CUT (TDM-100)	A	B	C	D	E	F
IMPACT	Pass			Fail		



### PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: (800) 262-5755 • (518) 861-0133 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobal.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.