



SPECIFICATION SHEET

305-5PVFR



ANSI TYPE R CLASS 2 FR TREATED SOLID BREAKAWAY VEST

- Solid polyester treated material to prevent after-flame
- Treatment lasts up to 25 washes
- 5-point breakaway provides additional safety around extreme traffic hazards, moving machinery or equipment
- FR 2" silver reflective tape
- 2 internal lower pockets
- 1 external chest pocket
- Hook & loop closure
- 2 internal lower pockets
- 1 upper left chest pocket
- Dual sized
- Tested to ASTM D6413

APPLICATIONS

- Road construction
- Survey crews
- Shipyards & railyards
- Anywhere high visibility and limited flammability is needed
- Not designed for use in an ARC flash or flash fire application

CARE INSTRUCTIONS

Machine wash in cold water, tumble dry low or hand dry. Do not iron, do not dry clean. Do not use bleach or fabric softener. Do not wash in biological powder, wash as synthetics. A chemical treatment is used to impart limited flammability that allows material to become self-extinguishing. Washing and wearing will diminish these properties.

TECHNICAL DATA

MATERIAL	100% Polyester
CONSTRUCTION	Main: 120gm/m ² treated polyester tricot Acc: 2" FR silver reflective tape, hook & loop closure
COLOR	■ Hi-Vis Yellow or ■ Hi-Vis Orange
SIZES	S/M, L/XL, 2X/3X, 4X/5X
PACKAGING	1 per poly bag, 5 per inner pack, 50 per case
CASE DIMENSIONS	18.9" x 14.2" x 16.1" / 48cm x 36cm x 41cm
CASE WEIGHT	41.9 lbs / 19 kg
COO	China

BARCODES

ITEM	BAG	INNER PACK	CASE
■ 305-5PVFRLY/S-M	616314069765	01616314069764	02616314069763
■ 305-5PVFRLY/L-XL	616314069758	01616314069757	02616314069756
■ 305-5PVFRLY/2X-3X	616314069734	01616314069733	02616314069732
■ 305-5PVFRLY/4X-5X	616314069741	01616314069740	02616314069749
■ 305-5PVFROR/S-M	616314096921	01616314096920	02616314096929
■ 305-5PVFROR/L-XL	616314096891	01616314096890	02616314096899
■ 305-5PVFROR/2X-3X	616314096907	01616314096906	02616314096905
■ 305-5PVFROR/4X-5X	616314096914	01616314096913	02616314096912



DIMENSIONS (in/cm)

	S/M	L/XL	2X/3X	4X/5X
A	47.2 / 120	52 / 132	56.7 / 144	61.4 / 156
B	28 / 71.1	28 / 71.1	28.9 / 73.5	29.9 / 76

