



SPECIFICATION SHEET

41-8035



G-TEK® POLYKOR® SEAMLESS KNIT SINGLE-LAYER POLYKOR/ACRYLIC GLOVE WITH DOUBLE-DIPPED LATEX COATED MICROSURFACE GRIP

- Seamless construction for a comfortable fit
- Polykor®/acrylic blended shell is lightweight and provides excellent dexterity, tactile sensitivity, cut resistance and economical cold weather protection
- Full latex coating helps keep hands dry in wet applications
- Latex MicroSurface coating provides a superior grip in dry and wet conditions by reacting like tiny suction cups that attach themselves firmly to the material being handled
- Double-Dipped coating helps extend the life of the glove and provides excellent abrasion resistance
- Single-layer construction provides excellent thermal insulation and improved dexterity
- Quickly evaporates moisture from the skin
- Knit wrist helps prevent dirt and debris from entering the glove
- Cotton color binding denotes sizing

APPLICATIONS

- Refrigerated areas
- Utilities
- Food processing
- Commercial fishing
- Construction
- Outdoor winter activities & recreation

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 104°F (40°C). A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low, maximum temperature 140°F (60°C).

TECHNICAL DATA

| | | | | | |
|-----------------|--|---------------------|---------------------|---------------------|---------------------|
| MATERIAL | Polykor™ / Acrylic Terry Shell; Double-Dip Latex Coating | | | | |
| COLOR | Shell: Salt & Pepper / Coating: Black & Blue | | | | |
| CUFF STYLE | Knit wrist | | | | |
| GAUGE | 10 | | | | |
| SIZES | S-2XL | | | | |
| PACKAGING | 1 pair per bag; 6 pair per inner pack; 6 dozen per case | | | | |
| CASE DIMENSIONS | 27.6" x 13.4" x 13" / 70cm x 34cm x 33cm | | | | |
| CASE WEIGHT | S | M | L | XL | 2XL |
| | 20.9 lbs 9.5 kg | 22.5 lbs 10.2 kg | 25.8 lbs 11.7 kg | 28.2 lbs 12.8 kg | 31.5 lbs 14.3 kg |
| CDO | China | | | | |

PERFORMANCE PROPERTIES

| | | | | | | |
|---------------|--|---|---|---|---|---|
| EN388: 3X42E | ASTM F2992-15 ANSI Cut Level A5 (Adopted by ANSI/ISEA 02/16) | | | | | |
| ABRASION | 0 | 1 | 2 | 3 | 4 | - |
| CUT | X | 1 | 2 | 3 | 4 | 5 |
| TEAR | 0 | 1 | 2 | 3 | 4 | - |
| PUNCTURE | 0 | 1 | 2 | 3 | 4 | - |
| CUT (TDM-100) | A | B | C | D | E | F |




BARCODES

| ITEM | PAIR | PACK | CASE |
|-------------|------|----------------|----------------|
| 41-8035/S | - | 01616314269287 | 02616314269286 |
| 41-8035/M | - | 01616314269294 | 02616314269293 |
| 41-8035/L | - | 01616314269300 | 02616314269309 |
| 41-8035/XL | - | 01616314269317 | 02616314269316 |
| 41-8035/XXL | - | 01616314269324 | 02616314269323 |

DIMENSIONS (in/cm)

| | S | M | L | XL | 2XL |
|---|----------|------------|-----------|------------|----------|
| A | 9.4 / 24 | 9.8 / 25 | 10.2 / 26 | 10.6 / 27 | 11 / 28 |
| B | 3.9 / 10 | 4.1 / 10.5 | 4.3 / 11 | 4.5 / 11.5 | 4.7 / 12 |
| H | Red | Yellow | Brown | Black | Blue |



PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: (800) 262-5755 • (518) 861-0133 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobal.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.